

Pro:Centric[®] SMART



webOS Commercial TV

LG Pro:Centric SMART offers webOS Commercial TV user interface and customizable tools that our partners can optimize their Hotel TVs with IP-based programs to provide premium hotel services with integrated set-top box solutions.


Simple Switching

webOS offers different user experiences with an intuitive user interface and fast response time.




Simple Customization

LG Commercial Smart Home will allow hotel sites to make their own Smart Home by selecting and ordering Apps with launcher based.



Simple Management

webOS provides remote diagnostics and signal monitoring via an embedded web server enabling SI or LG engineers to check TV or signal information easily.



Smart Customization

LG Pro:Centric SMART offers extended customizable tools; HTML5, Java and Flash with which our partners can optimize Hotel TVs to develop their own enhanced service design. Besides own designed essential TV service, guests can be served with bandwidth-worry-free pre-loaded applications without privacy concern thanks to LG's advanced history auto deletion S/W.

Customizable UI



Pre-loaded Application



History Auto-Delete



Extended Connectivity

Commercialized connectivity is ever revolutionized with Smart Share such as Smart Mirroring, WiDi and DLNA which enables guests to play and view content from their digital devices on their in-room TVs. Let your guests surf the internet just like at home with LG's easy-to-use Motion Remote controller and web-browser function.

Smart Mirroring/WiDi



Web Browser



Motion RCU




Pro:Centric[®] SMART

Specification


MODEL NAME		LY761H	LY760
Model information	Size (Inch)	32/39/42/47/55	
	Production Model	LY761H-ZA	LY760H-ZA
Broadcasting	Digital	DVB-T2 / C / S2	
	Analog	PAL / SECAM	
Video	Resolution	1920 x 1080 (FHD)	
Audio	Audio Output	10W+10W	
	Sound System	2.0ch	
Feature	Pro:Centric	Type	Pro:Centric SMART
		HCAP(GEM/FLASH/HTML)	GEM / FLASH / HTML5
	Smart	Commercial Smart Home	•
		Smart App.	•
	Connectivity	MHL	•
		Remote Diagnostics / Self Diagnostics	• (Remote Diagnostics)
	Management	EzManager	•
		HDMI-CEC	•
		HTNG-CEC 1.3	•
		Built-In Wifi	•
		Soft AP	•
		DRM	• (Pro:Idiom)
		Welcome Screen	•
Lock Mode		•	
Multi IR Code		•	
Hotel Mode		•	
USB Cloning	•		
Others	IR Out	•	
	USB Auto Play back	-	
	External Power	•	
	External Speaker Out	• (3.5mm, Stereo)	
	RJP Compatibility	• (RS232C,HDMI)	
Anti-theft System	Swivel	• ± 20°	-
	Kensington Lock	•	-
	Credeenza	•	-
Interface	Side	HDMI In	1
		USB (2.0)	2
		CI Slot	1
		Headphone Out	1
	Rear	RF In	2
		Digital Audio Out (Optical)	1
		Clock Interface (D-sub 15pin)	1
		RS-232C (D-Sub 9pin)	1 (Control & Service)
		HDMI In	1
		LAN Port	2
Power	External Speaker Out (3.5mm phone jack)	2 (Spk-out 1, Vol. Control 1)	
	Full Scart	1	
Standard Approval	Voltage, Hz	100 ~ 240V, 50 / 60Hz	
	Max (Watts)	32"(95W), 39"(124W), 42"(124W), 47"(127W), 55"(168W)	
	Typical(Watts)	32"(75W), 39"(100W), 42"(110W), 47"(120W), 55"(140W)	
	Energy saving (Min)	32"(46W), 39"(66W), 42"(66W), 47"(72W), 55"(98W)	
	Energy saving (Med)	32"(35W), 39"(43W), 42"(43W), 47"(47W), 55"(61W)	
	Energy saving (Max)	32"(25W), 39"(25W), 42"(27W), 47"(27W), 55"(30W)	
	Stand-by	0.3W↓	
Eco	Safety	CB,CE	
	Environment	ROHS, ErP, Eco flower	
Eco	ErP Class	A(32"/39"/42"), A+(47"/55")	
	On Power Consumption (IEC62097 Edition 2) (W)	39(32"), 54(39"), 55(42"), 56(47"), 80(55")	
	Stand By (W)	0.3	
	Luminance Ratio (%)	65	
	Mercury Content (mg)	0	
	Presence of Lead	Yes	
	Average Annual Consumption (kWh)	60(32"), 85(39"), 93(42"), 93(47"), 124(55")	

Dimension

LY761H(EU/MEA) : 32" / 39" / 42" / 47" / 55"




LY760H(EU/CIS/MEA) : 32" / 39" / 42" / 47" / 55"



	LY761H		LY760H	
Set (With Stand, WxHxD, mm) / Weight (With Stand, kg)	32"	732 x 482x 282/8.9	32"	732 x 481 x 207 / 6.2
	39"	885 x 572 x 282/10.9	39"	885 x 567 x 218 / 8.3
	42"	961 x 617 x 325/12.6	42"	961 x 610 x 218 / 9.5
	47"	1073 x 680 x 325/15.7	47"	1073 x 676 x 255 / 12.7
	55"	1243 x 771 x 325/21.4	55"	1243 x 772 x 255 / 18.4
Vesa Compatibility (mm)	32/39" : 200 x 200, 42/47/55" : 400 x 400			

Back Jack Panel



www.lgcommercial.com