

PC Built In Ready & Space Saving Solution LCD WIDESCREEN DISPLAY VS10

VS10 32" 42F" 47F"



PC BUILT IN READY

The embedded PC allows various functions to be performed without the need for messy cables and ensures easy installation & maintenance.



Internal Connection

SLIM DESIGN FOR SPACE SAVING

The Slot type Media Player completes the slim design of the VS10 and allows for more efficient use of space.

113mm + 45mm



External Media Player

113mm



Slot type Media Player

VS10

HIGH COMPATIBILITY

The VS10 is compatible with various Media Players.
(Model : NA2100, NA2000, NC2100)




IPS SUPERB PICTURE QUALITY

Model 42F" 47F"

NO BLACKENING DEFECT

Hardly affected by light or heat, hence no blackening.




IPS

Normal

TRUE WIDE

No color changes or distortion from any viewing angle.



IPS

Normal

STABLE PANEL

When touch the screen, it can also display consistently with leaving no mark.



IPS

Normal



LCD WIDESCREEN DISPLAY

VS10 32" 42F" 47F"



VS10 32" 42F" 47F"



FEATURES

- PC Built-in Ready : Easy Installation & Maintenance, Space Saving Solution
- Super IPS & Exclusive PD Panel
- USB Playback
- 42F", 47F" : 1,920 x 1,080 (FHD)
- High Scalability & High Compatibility

SPECIFICATIONS

PANEL	Screen Size	32", 42F", 47F"	SPECIAL FEATURES	Additional	Temp. Sensor, USB playback, Tile mode (Up to 5x5), ISM Method, Key Lock
	Panel Technology	42"/47" : IPS	ENVIRONMENT CONDITIONS	Operation Temperature	0 °C to 40 °C
	Aspect Ratio	16 : 9		Operation Humidity	10 % to 80 %
	Native Resolution	32" : 1366 x 768 (WXGA), 42"/47" : 1,920 x 1,080 (FHD)	POWER	Power Supply	100-240V~, 50/60Hz
	Brightness	32" : 450nit, 42"/47" : 500nit		Power Consumption	
	Contrast Ratio	32" : 3,000:1 (Typ), 42"/47" : 1,300:1		Typical/Smart Energy saving	32" : 100W(Typ), 42" : 200W(Typ), 47" : 240W(Typ)
	Dynamic CR	32" : 20,000:1, 42" : 40,000:1, 47" : 20,000:1		DPMS	1W(RGB), 1W(HDMI/DVI)
	Viewing Angle(H x V)	178 x 178		Power Off	0.5W
	Response Time	32" : 6.5ms (G to G), 42"/47" : 8ms (G to G, *WOT)	STANDARD(CERTIFICATION)	Safety	UL, cUL, CB scheme, TUV
	Input (Rear)			EMC	FCC Class "A", CE, KCC
CONNECTIVITY	Digital	HDMI/DVI(I) with HDCP		ErP / Energy Star	Yes / No
	Analog	32"/42" : Component(BNC I), Composite(BNC I), RGB(I) 47" : RGB/DVI(3.5ΦI), Component(RCA I), Composite(RCA I)	MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	Yes
	Audio	32"/42" : RGB/DVI(3.5ΦI), Component(RCA I), Composite(RCA I) 47" : RGB/DVI Audio, Component Audio(RCA), Composite Audio(RCA)		External Media player Attachable	32" : No, 42"/47" : Yes
	External Control	RS232C(I), RJ45(I)	SOFTWARE COMPATIBILITY	Supersign Compatibility	Elite-S, eZ-net Manager
	USB	Yes(I)	ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual, ESG
	Output (Rear)			Optional	32" : ST3210K (Stand), SP0000K (Speaker) 42"/47" : (Stand), SP0000K (Speaker)
	Digital	No			
	Analog	RGB(I), Composite(BNC I)			
	Audio	Composite(RCA I), External Speaker			
	External Control	RS232C(I)			
PHYSICAL SPECIFICATION	Bezel Width	32" : 51.5mm, 42" : 30.4mm, 47" : 36mm	* WOT : Within Operation Temperature ※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.		
	Monitor Dimension(W x H x D)	32" : 80.29cm x 49.30cm x 9.98cm 42" : 99.56cm x 58.76cm x 11.37cm 47" : 111.70cm x 66.10cm x 11.87cm	INTERFACE (32")		
	Weight(head)	32" : 13.2kg, 42" : 19.70kg, 47" : 28.80kg			
	Carton Dimensions(W x H x D) Head Only	32" : 89.5cm x 59.8cm x 18.9cm 42" : 112.0cm x 66.0cm x 28.5cm 47" : 120.3cm x 77.8cm x 33.2cm	(42F", 47F")		
	Packed Weight Head Only	32" : 13.98kg, 42" : 20.24kg, 47" : 31.53kg			
	VESA™ Standard Mount	32" : 200mmx200mm, 42" : 600mmx400mm, 47" : 800mmx400mm			

DIMENSION (unit : mm)

