


# Easy To Customize In Various Setting

## SEMI-OUTDOOR DISPLAY VX30AF



### SHINE OUT

Perfect fit for window display by reflecting away the sunlight for best image visibility and clearer display under direct sunlight than conventional panel.



BLU PANEL



VX30AF

### EASY TO CUSTOMIZE (OPEN FRAME)

VX30AF fits to any customer need and circumstance with its open frame. It can be designed according to customer request at an affordable price.



Front

Side

### MEDIA PLAYER INTEGRATED SOLUTION

The solution integrated with media player foregoes the need for additional media players and allows you to cut down expenses.



VX30AF




Free Software

## IPS SUPERB PICTURE QUALITY

### NO BLACKENING DEFECT

Hardly affected by light or heat, hence no blackening.




IPS

Normal

### TRUE WIDE

No color changes or distortion from any viewing angle.



IPS

Normal

### STABLE PANEL

When touch the screen, it can also display consistently with leaving no mark.



IPS

Normal

## SEMI-OUTDOOR DISPLAY

# VX30AF 47F"



## FEATURES

- Versatile applications in various setting
- Shine-Out
- Brightness : 700nit
- Front coverless open frame
- Super IPS & Exclusive PD Panel
- Power Consumption : 180W(Typ), 130(SES)
- USB Playback

## SPECIFICATIONS

PANEL	Screen Size	47"
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1920 x 1080 (FHD)
	Brightness	700nit
	Contrast Ratio	1,200:1
	Dynamic CR	3,000:1
	Viewing Angle(H x V)	178 x 178
	Response Time	8ms (G to G, *WOT)
CONNECTIVITY	Input (Rear)	
	Digital	HDMI(1), DVI(1), Display Port(1) with HDCP for all input
	Analog	Component(1), AV(1), RGB(1) (Shared with D-Sub)
	Audio	PC/AV/Component Audio In(1)
	External Control	RS232C(1), RJ45(1)
	USB	USB(1)
	Output (Rear)	
	Digital	DVI-D(1)
	Analog	Component(1), Composite(1), RGB(1) (Shared with D-Sub)
	Audio	External speaker
	External Control	RS232C
	PHYSICAL SPECIFICATION	Bezel Width
Monitor Dimension(W x H x D)		107.91cm x 62.42cm x 11.63cm
Weight(head)		22.4kg
Carton Dimensions(W x H x D)		118.2cm x 74.3cm x 26.9cm
Packed Weight		29.8kg
VESATM Standard Mount		800mm x 400mm

SPECIAL FEATURES	Additional	Shine-Out, Front cover less Open frame
ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~ 40°C
	Operation Humidity	10% ~ 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy saving on	180W(typ)/130W(Smart Energy Saving on)
	DPMS	1.0W (Set only)
	Power Off	0.5W
STANDARD(CERTIFICATION)	Safety	No (Should be qualified by set/ kiosk maker)
	EMC	No (Should be qualified by set/ kiosk maker)
	ErP / Energy Star	No (Should be qualified by set/ kiosk maker)
MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	No
	External Media player Attachable	Yes
SOFTWARE COMPATIBILITY	Supersign Compatibility	Yes
ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual
	Optional	ST1000K (Stand), SP0000K (Speaker)

\* WOT : Within Operation Temperature

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

## INTERFACE



**DIMENSION** (unit : mm)

