


Easy To Use In Various Setting SEMI-OUTDOOR DISPLAY VX30

VX30 42"/47"



SHINE OUT

Perfect fit for window display by reflecting away the sunlight for best image visibility and clearer display under direct sunlight than conventional panel.



VX30

MEDIA PLAYER INTEGRATED SOLUTION

The solution integrated with media player allows you to cut down the extra cost for a media player.



VX30



USB MULTI-MEDIA PLAYBACK

USB multi-media playback is simple, easy solution without additional cost.



USB Memory
(USB Multi-media playback)




Free Software
(SuperSign Elite-w lite)

IPS SUPERB PICTURE QUALITY

NO BLACKENING DEFECT

Hardly affected by light or heat, hence no blackening.




IPS

Normal

TRUE WIDE

No color changes or distortion from any viewing angle.



IPS

Normal

STABLE PANEL

When touch the screen, it can also display consistently with leaving no mark.



IPS

Normal

SEMI-OUTDOOR DISPLAY

VX30 42F", 47F"

VX30 42F", 47F"



FEATURES

- Shine-Out
- Brightness : 700nit
- Super IPS & Exclusive PD Panel
- USB Playback
- Power Consumption
42" : 170W(Typ)/130W(SES)
47" : 180W(Typ)/130W(SES)

SPECIFICATIONS

PANEL	Screen Size	42F", 47F"
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	700nit
	Contrast Ratio	1,200:1
	Dynamic CR	3,000:1
	Viewing Angle(H x V)	178 x 178
	Response Time	8ms (G to G, *WOT)
	CONNECTIVITY	Input (Rear)
Digital		HDMI(1), DVI(1), Display Port(1) with HDCP for all input
Analog		Component(1), AV(1), RGB(1) (Shared with D-Sub)
Audio		PC/AV/Component Audio In(1)
External Control		RS232C(1), RJ45(1)
USB		USB(1)
Output (Rear)		
Digital		DVI-D(1)
Analog		Component(1), Composite(1), RGB(1) (Shared with D-Sub)
Audio		External speaker
PHYSICAL SPECIFICATION	External Control	RS232C
	Bezel Width	42" : 16.9mm 47" : 17.9mm
	Monitor Dimension(W x H x D)	42" : 96.7cm X 55.98cm X 12.5cm 47" : 107.95cm x 62.46cm x 12.29cm
	Weight(head)	42" : 17.5kg, 47" : 22.2kg
	Carton Dimensions(W x H x D)	42" : 104.5cm x 66.0cm x 25.0cm 47" : 118.2cm x 74.3cm x 26.9cm
	Packed Weight	42" : 21.87kg, 47" : 29.6kg
	VESA™ Standard Mount	42" : 600mm x 400mm 47" : 800mm x 400mm

SPECIAL FEATURES	Additional	Shine-Out
	ENVIRONMENT CONDITIONS	Operation Temperature
POWER	Operation Humidity	10% ~ 80%
	Power Supply	100-240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy saving	42" : 170W(Typ)/130W(Smart Energy Saving on) 47" : 180W(Typ)/130W(Smart Energy Saving on)
	DPMS	1.0W(Set only)
STANDARD(CERTIFICATION)	Power Off	0.5W
	Safety	UL / cUL / CB scheme / TUV
	EMC	FCC Class "B" / CE / KCC
MEDIA PLAYER COMPATIBILITY	ERP / Energy Star	Yes / Yes (EPA 5.1)
	Slot PC compatible (optional)	No
SOFTWARE COMPATIBILITY	External Media player Attachable	Yes
	Supersign Compatibility	Yes
ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual
	Optional	42" : SP0000K (Speaker), ST0000K (Stand) 47" : SP0000K (Speaker), ST1000K (Stand)

* WOT : Within Operation Temperature

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

INTERFACE



DIMENSION (unit : mm)

