

Slim Design Affordable


32"/42"/47"/55"/65" FULL HD DISPLAY LS33A



**SLIM DESIGN**


Direct-LED panel featuring slim BLU offers stylishly slim monitors designed to fit perfectly into narrow spaces in retail shops while ensures high energy efficiency

Slim Design



**PORTRAIT/LANDSCAPE MODES**


Portrait/Landscape Scene available



**COST-EFFECTIVE SOLUTION**

SuperSign embedded player is suitable for running simple content in an effort to save cost and ease of installation and maintenance as well


No need for an additional media player



**REMOTE CONTROL VIA RS232C & NETWORK**

SuperSign embedded player with RJ45 interface allows easy content transfer and control via network

Network based content control



# LS33A SERIES 32", 42", 47", 55", 65"



## FEATURES

- Brightness: 300nit(32"/42"/47"), 330nit(55"), 350nit(65")
- Direct-LED Display
- Portrait/Landscape Orientation
- Embedded Media Player
- Vertical Retail Targets : SMB (Small & Medium Business), Retailers
- Energy Star 6.0 Compliant
- IPS Panel
- Low Screen Temperature
- No Blackening Defect
- Wide Viewing Angle



## SPECIFICATIONS

		LS33A					
PANEL	Screen Size	32", 42", 47", 55", 65"		PHYSICAL SPECIFICATION	Monitor Dimension (W x H x D)	32": 73.0cm x 42.9cm x 5.5cm 42": 96.0cm x 56.0cm x 5.5cm 47": 107.0cm x 62.0cm x 5.58cm 55": 123.8cm x 71.2cm x 5.68cm 65": 146.0cm x 84.0cm x 5.76cm	
	Panel Technology	IPS			Weight (Head)	32": 5.6kg / 42": 9.0kg / 47": 12.5kg / 55": 17.6kg / 65": 34kg	
	Native Resolution	Full HD (1920X1080)			ENVIRONMENT CONDITIONS	Operation Temperature	0 °C to 40 °C
	Brightness	32"/42"/47": 300nit / 55": 330nit / 65": 350nit				Operation Humidity	10 % to 80 %
	Contrast Ratio	32"/42"/47": 1,200:1 / 65": 1,400:1			POWER	Typical / Smart Energy Saving	33" : 45W / 28W 42" : 65W / 38W 47" : 80W / 65W 55" : 85W / 67W 65" : 200W / 140W
	Dynamic CR	500,000:1					STANDARD (CERTIFICATION)
	Viewing Angle (H x V)	178 x 178			MEDIA PLAYER COMPATIBILITY	EMC	
	Response Time	9ms(G to G BW)				SOFTWARE COMPATIBILITY	ErP / Energy Star
CONNECTIVITY	Input (Rear)	Digital	HDMI(1), DVI-D(1), DP(1)	ACCESSORY	included		Remote Controller(include battery 2ea), Power Cord, IR Receiver, CD(Owner's Manual, SuperSign Program / Manual), RGB Cable
		Analog	RGB(1)				
		USB	Yes(1)				
	Output	Digital	-				
External Control	Audio	RGB(1)	Yes(1)				
PHYSICAL SPECIFICATION	Bezel Width	32": (R/L) 10.5mm(15.1mm for rearmost spot) (T) 10mm(14.6mm for rearmost spot) (B) 14mm(18.6mm for rearmost spot)		PHYSICAL SPECIFICATION	Bezel Width	32": No / 42": 47": 55": 65": Yes (MP500/MP700)	
		42": (R/L/T) 8.5mm(13.3mm for rearmost spot) (B) 14mm(18.8mm for rearmost spot)					
		47": (R/L/T) 8.5mm(13.2mm for rearmost spot) (B) 14mm(18.7mm for rearmost spot)					
		55": (R/L/T) 8.5mm(13.2mm for rearmost spot) (B) 14mm(18.7mm for rearmost spot)					
		65": (R/L/T) 9mm(14mm for rearmost spot) (B) 14.6mm(20mm for rearmost spot)					

## DIMENSION (unit: mm)

