LG COMMERCIAL MONITOR

PROFESSIONAL

65VS10

- •Resolution : 1,920 x 1,080(FHD)
- •Exclusive PD Panel









SPECIFICATION

PANEL

Screen Size: 65"

Aspect Ratio : 16 : 9 Native Resolution: 1920 x 1080 (FHD)

Brightness: 700cd/m²

Contrast Ratio: 2,500:1, 5,000:1 (DCR) Viewing Angle (H x V) : 178 x 178

Response Time: 8 ms (G to G)

AUDIO

Audio Power: 20W (10W x 2)


Speaker On/off : Yes Clear Voice : Yes

Sound mode: Standard / Music / Cinema / Sports / Game / User


CABINET

Bezel Width: 49.0 mm

DIMENSION








FEATURES

24/7 Operation Performance

Another strength of the LG PD module is that it can operate 24 hours a day. It can fulfill its function as a digital signage, smashes the limits of place and time and is highly durable and provides continuous performance.






The portrait display mode is the exclusive area of the PD module. The pressure exerted by the liquid crystal is generally proportional to the distance from the top of the screen. Therefore the maximum pressure is exerted at the bottom of screen while the minimum pressure is exerted at the top of the screen. However, the PD module has relatively uniform pressure distribution com-





paring to TV panel, which in consequence has a far better stability.






No Blackening Defect

Even under direct sunlight exposure, LG commercial monitors that adopted LGD V5 panel remain free of blackening defects and provides superior quality for outdoor usage. This means you can save on costs related to purchasing IR blockers or extra cooling systems, in addition to saving power. What's more, you can save on space since no glass covers are needed for the monitors.








Enhanced Scheduler

The upgraded scheduler lets the user set the 'On' and 'Off' time from Monday through Sunday. So you can flexibly manage the operation time of the LG commercial monitors.







SPECIFICATION

	65VS10
Screen Size	65"
Aspect Ratio	16 : 9
Native Resolution	1920 X 1080 (FHD)
Pixels(H x V x 3)	6,220,800
Brightness	700 cd/m ²
Contrast Ratio	2,500 : 1, 5,000:1 (DCR)
Viewing Angle(H x V)	178 x 178
Color Depth	1.07 Billion
Response Time	8 ms(G to G)
Surface Treatment Max Input Resolution	HCLR, Hard Coating(3H) 1920 X 1080 @ 60Hz(RGB, HDMI/DVI)
Recommended Resolution	1920 X 1080 @ 60Hz (RGB, HDMI/DVI)
H-Scanning Frequency	30 ~ 83kHz (RGB, HDMI/DVI) 56 ~ 75 Hz (RGB), 60Hz (HDMI/DVI)
V-Scanning Frequency Pixel Frequency	148.5 MHz (RGB, HDMI/DVI)
Sync Compatability	Separate / Composite / Digital
Video Input	RGB, HDMI / DVI
Picture Mode	Vivid/Standard/Cinema/Sports/Game/User1/User2
Color Temperature	Warm / Medium / Cool / User
Component Video	1Hi-Res
PC Input via 15-Pin Sub "D"	1/1
Composite Video Input / Output	1/1
Audio Output	1
Audio Inputs	2 Plus PC Sound
HDTV Formats	Component : 720p/1080i/1080p HDMI : 720p/1080i/1080p
PC Formats	Auto Scaling to FHD
HDMI / DVI with HDCP	Yes
RS-232C Input / Output	1 / 1, Female-to-Female Crossed Type
RJ-45	Yes
USB	Yes
Audio Jack Built-in(No Amp)	Yes
Discrete IR Input	Yes
Auto Volume	Yes
Balance	Yes
Audio Power	20W(10W x 2)
Speaker On/off	Clear Voice/Standard/Music/Cinema/Sports/Game/User
Sound Mode NC2000(Optional PC) Compatible	No
New Temperature Sensor	Yes
Tile Mode	Yes, Up to 5x5, support natural mode
Image Zoom	No
Source Selection	Digital(HDMI/DVI) / Analog(RGB) / Component /
Brightness/Contrast	Yes
Position	H / V
Set-up	Language (English / French / Spanish / Italian / German / Portugues
ISM Method	Korean / Japanese / Chinese / Russian) Normal/White wash/Orbiter/Inversion/Dot wash
Advanced	Gamma / Film mode /
Advanced	Black level / Noise Reduction
Auto Power/Source Memory	Yes
Key Lock	Yes
Color	Black
Bezel Width	49.0 mm
Monitor Dimensions(W X H X D)	153.54cm (60.5") X 90.76cm (35.7") X 13.67cm (5.4")
Weight	52kg (114.6 lb)
Monitor with Optional Stand	N/A : No Speaker
& Speaker Dimensions(W X H X D)	
Carton Dimensions(W X H X D)	169.0cm (66.5") X 103.0cm (40.6") X 33.0cm (13.0 (Head Only)
Packed Weight	59.6kg (114.6 lb) (head only)
VESA TM Standard Mount Interface (mm)	600 x 400 (AP-WX60)
Power Supply	100-240V~, 50/60Hz
Power Type	Built-in Power
Power Switch	No
Power Consumption Normal	550 W
DPMS	1W(RGB) / 2W(HDMI/DVI)
Power Off	1W
Safety	UL / c-UL / CB scheme / TUV

FCC Class "B" / VCCI / C-tick / CE / KCC

*The specification could be changed without prior notice.