

PK250N

Plasma TV



Specifications

Sizes	60"/50"	Zoom +/-, Screen position	●
Plasma Specifications		Picture Reset	●
Resolution	1920x1080p	Picture Mode	8 Mode (Vivid/Standard/APS/Cinema/ Sports/Game/isf Expert1/ isf Expert2)
Brightness (cd/m²)	1500	PC Resolution	1920x1080 @ 60 Hz
Contrast Ratio	3,000,000:1	Audio	
600 Hz Sub-field Driving	●	Mono/Stereo/Dual (MTS/SAP)	●/●/●
Filter Type (X-Black/Glass)	Glass	Audio Output (Watts – TDH 10%)	10 W + 10 W
Broadcasting System		SubWoofer	–
DVB-T/DVB-C	●	Speaker System	1 way 2 speaker
Video		Dolby Digital Decoder	●
Dual XD Engine	●	Surround System	Infinite Sound
Aspect Ratio	16:9	Bass/Treble/Balance	●/●/●
Enhanced Noise Reduction	3D Noise Reduction (High/Mid/Low/Off)	Mute	●
Color Temperature Control	● (Cool/Medium/Warm)	USB 2.0	
Real Cinema 24p (3:3 pull down)	● (HDMI 1080 24p)	MP3	–
Cinema 3:2/2:2 Pull down Mode	●		

JPEG	–
MPEG 2/4	–
Device (included USB Hub)	–
Subtitle for DivX	–
Special	
WiFi/DLNA	–
THX	–
Picture Wizard	●
Intelligent Sensor	●
EPG (SI)	●
Wireless Built-in	–
Wireless Ready	–
Bluetooth	–
CIFS (PC Contents Sharing)	–
Broadband	–
e-Manual	●
Moving Picture Playback	–
Picture Mute	●
Energy Saving Mode (+ Module DPM)	●
Clear Voice II (Voice Zoom)	●
AV Mode	●
1080p Source Input	HDMI 60p/50p/30p/24p Component 60p/50p
AV Input Navigation (Auto Link)	●
Input Labelling	●
Screen Adjust/Auto (Manual) Configure – only RGB signal	●
Quick View (Flash Back)	●
Picture Freeze	●
Rating (DTV)	●
Key Lock	●
Simplink (HDMI CEC)	● (All HDMI)
Teletext	
Pages	Max 2000
Jack Pack – Side	
AV In	–
S-Video In	–
RGB in (D-sub 15 pin)	–
PC Audio Input	–
HDMI in	● (1) (HDMI 1.3, Simplink)
CI Slot	All Europe
USB 2.0	● (SVC Only)

Jack Pack – Rear	
RF In	● (1)
AV In	–
AV Out	–
S-Video In	–
Full Scart	● (1) (TV out)
Half Scart	● (1) (MNT/DTV Out)
Component in (Y, PB, Pr) + Audio	● (1) (480i/480p/576i/576p/ 720p/1080i/1080p)
Digital Audio Out	● (1) (Optical)
Variable Audio Out	–
HDMI/HDCP Input	● (1) Ver. 1.3 (480i/480p/576i/576p/720p/1080i/1080p) – 1 Port PC Mode – SIMPLINK
DVI Input	–
IEEE 1394/DTCP	–
RGB In (D-sub 15 pin) – PC	–
PC Audio Input	● (1 for DVI)
Lan (For Modem)	–
RS-232C (Control/SVC)	● (1) – CONTROL & SVC
Remote Control In Port	–
Headphone In	–
Cabinet Description	
Swivel (*)	● (20/20)
VESA Size	60": 600x400 50": 400x400
Dimensions	
Weight (kg)	60": 41,4
Set (w/o stand)	50": 28,6
Weight (kg)	60": 45,9
Included stand	50": 31,0
Weight (kg)	60": 54,9
Packing (w/ stand)	50": 34,2
WxHxD (mm)	60": 1392x843x55,3
Set (w/o stand)	50": 1171,4x720,9x55,3
WxHxD (mm)	60": 1392x910x384
Included stand	50": 1171,4x781,8x309,7
WxHxD (mm)	60": 1529x1058x499
Packing (w/ stand)	50": 1314x821x314
Power	
Consumption (IEC62087 dynamic broadcast-content video signal) / APS mode	60": 234 W 50": 190 W
Standby (Stand by mode)	0,1 W

