

LOOKBOOK

Food Retail



Brand Potato Chips



points!









3 LAYERS OF CHEESE ONLINE EXCLUSIVE: CHOOSE ANY SIDE MENU FOR FREE





Introduction

A network of digital signs can be a real game changer by giving grocers powerful basket-building tools to promote products, brands, LTO's and specific day-parted promotions that create new upsell and impulse purchase opportunities.

Placed at entrances free-standing displays provide navigation and wayfinding, drive traffic to prepared food keeping buffets fresh, help decision making at the deli counter, at beer cave displays that attract add-on sales, and create stress-free check-lanes.

Available in a wide variety of shapes, sizes and technologies, LG commercial displays deliver optimum results throughout, and even outside, the store and are designed to deliver years of service with little maintenance.



a Smart Platform Digital Touchscreen Signage -49TA3E

- 49" IPS Touchscreen
- Resolution: 1920 x 1080 (FHD)
- Brightness: 450 nits
- Viewing Angle: 178 x 178
- Bezel Width: 32.7mm (Even)
- VESA mount: 300 x 300
- PCB Conformal Coating
- Temperature Sensor
- Auto Brightness Sensor
- Easy Brightness Control
- Tile Mode (Up to 15x15)
- 10-point multitouch
- webOS with SKD supports HTML5
- Smart Energy Saving
- File Play with USB
- PIP (Picture-in-Picture)
- PBP (Picture-by-Picture)
- Internal Memory 8GB
- Wi-Fi Built-in (802.11n combo)
- Beacon and Bluetooth Low Energy
- USB Cloning
- IDB Whiteboard AppBuilt-in Speaker (10W+10W)
- 24/7 operation
- Portrait and Landscape orientation





a Ultra-Stretch Signage- 86BH5C • 86" Class (85.6" diagonal) • IPS Panel Technology

- 3840 x 600 Ultra HD Resolution
- 58:9 Extended Wide Format
- 4 Divided PBP in Landscape or Portrait
- Brightness 500 nits, Min : 400 nits
- Built-in SoC and Synced Playback
- Portrait and landscape orientation • Pedestal types: Single, double, triple
- and 4-sided. NOTE: Some pedestals supplied by third-party system integrator.



please your palate \$8.99





Smart Platform Digital Signage - 49SM5KD 49" Class (48.5" diagonal) Resolution: 1920 x 1080 (FHD)

- Brightness: 450 nits
- Bezel 11.9 mm (T/R/L), 18 mm (B)
- PBP (Picture-By-Picture)
- PIP (Picture-In-Picture)
- Quad Core SoC
- webOS 3.0
- IP Streaming Protocol
- Dust & Humidity Protection
- SuperSign Premium
- 24/7 operation
- Portrait and landscape orientation

b Open-Frame Curved OLED Signage - 55EF5E

- 55" Class
- Resolution: 1920 x 1080 (FHD)
 Brightness: 150/400 nits (APL100% / 25%) average picture level
- Available in arched, curved, concave and convex by using LG OLED Module / Signage Box and T-Con Box / Cables
- Maximum Curvature in Portrait: 1,500R Radius: 1,000mm Circumference: 9,420mm
- Maximum Curvature in Portrait: 1,000R for Concave/Convex





a Smart Platform Digital Touchscreen Signage -32TA3E

- 32" IPS Touchscreen
- Resolution: 1920 x 1080 (FHD)
- Brightness: 450 nits
- Viewing Angle: 178 x 178
- Bezel Width: 32.7mm (Even)
- VESA mount: 200 x 200
- PCB Conformal Coating
- Temperature Sensor
- Auto Brightness Sensor
- Easy Brightness Control
- Tile Mode (Up to 15x15)
- 10-point multitouch
- + webOS with SKD supports HTML5 $\,$
- Smart Energy Saving
- File Play with USB
- PIP (Picture-in-Picture)
- PBP (Picture-by-Picture)
- Internal Memory 8GB
- Wi-Fi Built-in (802.11n combo)
- Beacon and Bluetooth Low Energy
- USB Cloning
- IDB Whiteboard App
- Built-in Speaker (10W+10W)
- 24/7 operation
- Portrait and Landscape orientation
- NOTE: Custom VESA stand manufactured by third party.



MEAL KIT No.15

acorn squash with apple cider vinegrette








a Smart Platform Digital Touchscreen Signage -32TA3E

- 32" IPS Touchscreen
- Resolution: 1920 x 1080 (FHD)
- Brightness: 450 nits
- Viewing Angle: 178 x 178
- Bezel Width: 32.7mm (Even)
- VESA mount: 200 x 200
- PCB Conformal Coating
- Temperature Sensor
- Auto Brightness Sensor
- Easy Brightness Control
- Tile Mode (Up to 15x15)
- 10-point multitouch
- webOS with SKD supports HTML5
- Smart Energy Saving
- File Play with USB
- PIP (Picture-in-Picture)
- PBP (Picture-by-Picture)
- Internal Memory 8GB
- Wi-Fi Built-in (802.11n combo)
- Beacon and Bluetooth Low Energy
- USB Cloning
- IDB Whiteboard App
- Built-in Speaker (10W+10W)
- 24/7 operation
- Portrait and Landscape orientation
- NOTE: Cabinet frame supplied by third-party integrator.









Images are simulated.



a Ultra Stretch Display - 88BH7D • 88" Class (87.80" diagonal) • Resolution: 3840 x 1080 (UHD)

- Brightness: 700 nits
- IPS Panel Technology
- 32:9 aspect ratio
- Stand-alone
- Instalation types: Stand alone, Tri-Sided, Quad-Sided, Video wall 360-degree video column
- Touch-Screen
- 4x Picture-in-Picture





a Smart Platform Digital Signage - 55SM5KE • 55" Class IPS Screen

- Resolution: 1920 x 1080 (FHD)
- Brightness: 450 nits
- Viewing Angle: 178 x 178
- Bezel Width: 11.9 mm (T/R/L), 18 mm (B)
- VESA mount: 200 x 200
- PCB Conformal Coating
- Temperature Sensor
- Auto Brightness Sensor
- Easy Brightness Control
- Tile Mode (Up to 15x15)
- webOS 4.0
- Smart Energy Saving
- PIP (Picture-in-Picture)
- PBP (Picture-by-Picture)
- Internal Memory 8GB
- Wi-Fi Built-in
- Beacon Enabled
- Built-in Speaker (10W+10W)
- 24/7 operation
- Portrait and Landscape orientation

Bacon Egg and Cheese Breakfast Biscuit Sandwiches Mediterranean Vegetable Mediterranean vegetable

a

6

Veggie Panini provolone chiese, egg plans, oxen roasted tomato, freshkale grilled zucchini, avocado spread

Tuna Salad Wrap eggs, capers, giardiniera, red onion, lettuce: torrato, m

Baja Chicken monterrey jack cheese, roasted peppers, lettuce, tomato, avocado spread, brioche hun









- Smart Platform Digital Signage 55SM5KE
 55" Class IPS Screen
 - Resolution: 1920 x 1080 (FHD)
 - Brightness: 450 nits
 - Viewing Angle: 178 x 178
 - Bezel Width: 11.9 mm (T/R/L), 18 mm (B)
 - VESA mount: 200 x 200
 - PCB Conformal Coating
 - Temperature Sensor
 - Auto Brightness Sensor
 - Easy Brightness Control
 - Tile Mode (Up to 15x15)
 - webOS 4.0
 - Smart Energy Saving
 - PIP (Picture-in-Picture)
 - PBP (Picture-by-Picture)
 - Internal Memory 8GB
 - Wi-Fi Built-in
 - Beacon Enabled
 - Built-in Speaker (10W+10W)
 - 24/7 operation
 - Portrait and Landscape orientation

b Ultra HD Premium Large Display - 98LS95D

- 98" Class (97.5" diagonal)
- IPS Panel Technology
- 3840 x 2160 {UHD} Resolution
- Brightness 500 nits {Typ}
- Contrast Ratio 1300:1
- Response Time 8ms {G to G BW} typ.
- Temperature sensor
- Auto brightness sensor
- Tile mode (up to 15x15)
- Smart Energy saving
- File play with USB
- PIP (Picture-in-Picture)
- PBP (Picture-by-Picture)
- Internal memory (8 GB)
- Beacon Enabled
- 24 hours Operation
- Landscape & Portrait Orientation





Ultra-Stretch Signage- 86BH5C 86" Class (85.6" diagonal)

- IPS Panel Technology
- 3840 x 600 Ultra HD Resolution
- 58:9 Extended Wide Format
- 4 Divided PBP in Landscape or Portrait
- Brightness 500 nits, Min : 400 nits
- Built-in SoC and Synced Playback
- Portrait and landscape orientation • Pedestal types: Single, double, triple
- and 4-sided NOTE: Some pedestals supplied by third-
- party system integrator.





a Ultra Narrow Bezel Video Wall - 55VH7B-H


- 55" Class (54.7"" diagonal)
 Resolution: 1920 x 1080 (FHD)
- Brightness: 700 nits
- Tile Mode up to 15 x 15 (Natural mode)
- IPS Panel Technology Bezel Width 0.9mm (Even)
- Running Time: 24 Hours
- Portrait and landscape orientation
- SuperSign W / SuperSign C





Smart Platform Digital Signage - 32SM5KE 32" Class IPS Screen

- Resolution: 1920 x 1080 (FHD)
- Brightness: 400 nits
- Viewing Angle: 178 x 178
- Bezel Width: 13 mm (T/R/L), 18 mm (B)
- VESA mount: 200 x 200
- PCB Conformal Coating
- Temperature Sensor
- Auto Brightness Sensor
- Easy Brightness Control
- Tile Mode (Up to 15x15)
- webOS 4.0
- Smart Energy Saving
- PIP (Picture-in-Picture)
- PBP (Picture-by-Picture)
- Internal Memory 8GB
- Wi-Fi Built-in
- Beacon Enabled
- Built-in Speaker (10W+10W)
- 24/7 operation
- Portrait and Landscape orientation





a Ultra-Stretch Signage- 86BH5C 86" Class (85.6" diagonal) IPS Panel Technology 3840 x 600 Ultra HD Resolution

- 58:9 Extended Wide Format
- 4 Divided PBP in Landscape or Portrait
- Brightness 500 nits, Min : 400 nitsBuilt-in SoC and Synced Playback
- Portrait and landscape orientationPedestal types: Single, double, triple
- and 4-sided NOTE: Some pedestals supplied by third-party system integrator.





a SuperSign™ Smart TV - 55LV640S • 55" Class 54.9" diagonal • 1920 x 1080 (FHD)

- Brightness 400 nits
 SuperSign Simple Editor, SuperSign Lite
 Simple Editor
- Clear Voice
- Panel Contrast Ratio: 1100:1
- Aspect Ratio: 6 modes (16:9, Just scan, Set by program, 4:3, Zoom, Cinema zoom1)
 webOS 3.5
- Web Browser
- Commercial Smart Home
- Pre-loaded YouTube Apps
- VESA Mount: 300 x 300
- Internal Speakers: 10W x 2





Direct View LED Outdoor Display - LBP Series
Brightness (After Calibration): 6000 nits minimum
Viewing Angle: 160°

- Contrast Ratio: 3000:1
 Lifetime (half brightness): 100,000 hrs
 Pixel Pitch: 6.00 20.00
 Weight per Module (kg): 0.54 2.45





- Outdoor Display 75XE3C
 75" Class 74.5" (diagonal)
 Resolution: 3840 x 2160 (UHD), M+
 - Brightness: 3000 nits (Typ) 2400 nits (Min) through protective glassContrast Ratio: 1200:1

 - Surface Treatment Hard coating (2H), Anti-glare treatment of the front polarizer (Haze 3% (Typ.)
 Operation Temperature: -22 °F to 122 °F
 Operation Humidity: 5 % to 100 %
 Use in Direct Sunlight
 IP56 rated for Dust / Water Resistance





a Colored LED Transparent Film - LAT240DT1

- Pixel Pitch: 24mm
- Pixels per LED Film Sheet: 560 pixels
- Brightness: 1,000 nits minimum (After Calibration)
- Lifetime (Brightness 50%): 50,000 hrs





Specific Applications for Signage

LG's signage fits into applications ranging from wayfinding to computer labs – with full software and technological support available.

Wayfinding

From simple maps to interactive touch screens with compatible apps for off-loading directions, wayfinding solutions are as simple or as complex as needed. And with touchscreen and mobile integration through apps on webOS, interactive and indoor mapping has never been easier.

Scheduling

webOS supports real-time data integration so that you can create real-time class and room schedules, sports scores and even IPTV or web pages. Connect with documents and data sources like Excel, SAP and MS Exchange to share real-time developments and information.

Digital Menu Boards

Save paper and ink with energy-efficient digital displays where you can update and customize content in real-time. With remote management staff can quickly make changes and update all screens from a central location.

Advertising

Earn funds with sponsor, donor and business promotions. Food Retails environments across the country already accept advertisements from local to national brands to promote and earn money for their stores.

Conclusion

LG's digital signage products and solutions not only engage customers but have been proven to uplift sales when displaying promotions, advertising, cross-selling, and target marketing. Our award-winning products and solutions operate efficiently, are easy to integrate into current systems, and can be remotely managed to keep things fresh from wherever your systems are managed.

We offer a custom approach to each installation making sure to meet the challenging needs of different Food Retailer's environments.



To download this Lookbook's complimentary infographic.



LG Electronics U.S.A, Inc. | HE B2B Division | 2000 Millbrook Drive | Lincolnshire, IL 60069

All images on screen are simulated. Design, specifications, and features subject to change without notice. © Copyright 2018 LG Electronics USA, Inc. All rights Reserved. LG Life's Good, ProCentric and XD Engine are registered trademarks of LG Corp. ProJdiom is a registered trademark of Zenith Electronics Corporation. All other product and brand names are trademarks or registered trademarks of their respective companies

LOOKBOOK_FoodRetail_081848_a