



HOSPITALITY

Direct LED

Commercial Widescreen Integrated HDTV

▶ 55LN541C

55" class (54.6" measured diagonally)

▶ 47LN541C

47" class (46.9" measured diagonally)

▶ 42LN541C

42" class (41.9" measured diagonally)

▶ 32LN541C

32" class (31.5" measured diagonally)



Optimized Features for Commercial Use

FOR EFFICIENT MANAGEMENT



PUBLIC DISPLAY MODE
From channel selection to energy-saving features,
Public Display Mode allows you to control the TV settings in your business area prevent misuse by customers, set volume limits, or restore factory defaults on any TV. You are in control of it all.





USB CLONING

The USB Cloning feature allows you to simply copy the TV settings onto all TVs using a USB stick, a process that is fully automated to save time without having to set each TV one by one.





WELCOME SCREEN

Welcome visitors with a warm greeting message that includes your business name and logo.





MULTI IR

Multi IR function eliminates the remote control signal interference between TVs in multiple dwelling rooms. This system will work using the same LG TV model.

(Optional 124-213-10 required)





RS232C CONTROL

Via the TV's RS-232C port, you can remotely control multiple TVs' power and volume settings



FOR CONVENIENCE & ENTERTAINMENT



EXTERNAL SPEAKER OUT
Enhance the entertainment experience by adding an additional speaker, visitors to listen to and control the TV audio from anywhere in your business area, including restrooms.





IR OUT
IR Out enables customized set-top boxes to receive IR signals via LG TV Signage. This added convenience allows easy management using a single remote control.





REMOTE JACK PACK
The plug and play function with compatible Remote Jack Pack enables guests to view media from their portable devices on the TV screen seemlessly.





You can play images and videos from and record TV programs to external storage devices. Immediate recording and reserved recording options are available





Direct LED

Commercial Widescreen Integrated HDTV

▶ 55LN541C

55" class (54.6" measured diagonally)



47" class (46.9" measured diagonally)



42" class (41.9" measured diagonally)

32LN541C

32" class (31.5" measured diagonally)

Model Hotel Mode/ PDM /Installer Menu RJP Compatibility

USB

Moving Picture Playback (SD/HD/Plus HD)

Audio Codec

USB Cloning

Multi IR Code

Welcome Screen

Auto Off / Auto Sleep

Video Mute Smart Energy

Saving Anti-theft System

USB (2.0)

Digital Audio Out (Coaxial / Optical)

HDMI/HDCP

RGB In (D-sub

PC Audio Input

RS-232C (D-Sub

External Speaker Out (3.5mm phone

Without Stand

VESA™ Standard

Mount Interface Credenza Bracket Flame Retardant

Energy Star 6.0

Power Source Typical (Watts)

Stand-by

46.7 lbs

42.1 lbs

59.5 lbs

86.2W

1.5-Year Limited Warranty (Parts/Labor/Backlight)

15pin) - PC

RF In

AV In

Input

9pin) RJ45 (RJP interface)

jack) With Stand

Weight

Weight

Carton

Weight

Swivel

Color


Safety

RoHS

REQUIRED LISTINGS

UPC

INPUTS/ OUTPUTS



PANEL	Model	55LN541C	47LN541C	42LN541C	32LN541C	
	Backlighting	Direct LED				
	LCD Panel Type	55" Class (54.6" measured diagonally)	47" Class (46.9" measured diagonally)	42" Class (41.9" measured diagonally)	32" Class (31.5" measured diagonally)	
	Native Resolution	1920 x 1080 (FHD) 1366			1366 x 768 (HD)	
	Brightness	300cd/m ²				
	Dynamic CR	1,000,000:1				
	Viewing Angle (HxV)	178°/178°				
	Response Time	9ms				
	Frame Rate	60Hz				
VIDEO	Built-In Tuner	ATSC/NTSC/Clear QAM				
	XD Engine	Yes				
	24p Real Cinema (24p 5:5/2:2 Pull down)	Yes				
	Eye Care (Anti Dazzling)	Yes				
AUDIO	Audio Output	20W (10W x 2)				
	Speaker System	1 Way 2 Speakers				
	Infinite Sound	Yes				
	Invisible Speaker	Yes				
	Clear Voice II	Yes				
SPECIAL FEATURES	RF(1/2Tuner)	Yes (1 Tuner)				
	Simplink	Yes (HDMI-CEC)				
	SI Compatible (TVLink Protocol)	Yes (TV Link Tuner)				

	The estimated annual energy cost determined in accordance with 16 CFR Part 305.5 for models 55LN541C, 47LN541C,
EMERGY	42LN541C and 32LN541C are \$17, \$15, \$12 & \$8 respectively.
UIDE↓	"Your energy cost depends on your utility rates and use. The estimated cost is based on 11 cents per kWh and 5 hours of use per d For more information, visit www.ftc.gov/energy."
JOIDE .	FEC Television Inheling rule (18 CFR Part 305, as added by 76 Fed. Reg. 1038 (Ian. 6, 2011))



Life's Good

LGsolutions.com

LG Electronics U.S.A., Inc. HE B2B Division 2000 Millbrook Drive Lincolnshire, IL 60069

Customer Service: 888.865.3026 www.LGsolutions.com/support

Contact your LG Regional Sales Representative: Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com

SPEC_LN541CSeries_041309_PR








72.3W

@ Copyright 2013 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp.

ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency, In Plane Switching is a trademark of LG Display Co., LTD. VESA is a trademark of Video Electronics Standards Association. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.











55LN541C 47LN541C 42LN541C 32LN541C

LG, Teleadapt (RJ45, HDMI CEC), G-Link(HDMI-CEC)

USB2.0, USB Auto Play back, USB Cloning

Divx HD

JPEG

AC3(Dolby Digital), EAC3, AAC, Mpeg, MP3, PCM

USB 2.0

Yes

Yes

Yes

Yes

Kensington Lock

1 Side

1 Rear

1 Rear

1 Rear (Optional)

3 (2 Rear, 1 Side)

1 Rear

1 (Sharing with AV In)

1 Rear

1 Rear

1 Rear

49.2" x 31.1" x 11.7" 42.5" x 27.3" x 10.4" 38.1" x 24.8" x 9.3" 29.1" x 19.6" x 8.1"

Black with Hairline Finish

Yes (Back Cover only)

cUL, UL, NOM, FCC

Yes

Yes

7 19192 91558 9 7 19192 91557 2 7 19192 91556 5 7 19192 91555 8 100~240V 50/60Hz

0.5W

23.6 lbs

21.2 lbs

31.3 lbs

±90°

200 x 200mm

15.4 lbs

 $29.1'' \times 17.7'' \times 3.1''$

35.5" x 20.9" x 6.4"

20.3 lbs

±15°

200 x 100mm

32.0 lbs

 $49.2'' \times 29.0'' \times 3.1'' \quad 42.5'' \times 25.3'' \times 3.2'' \quad 38.1'' \times 22.8'' \times 3.1''$

28.9 lbs

61.0" x 33.1" x 8.3" 52.4" x 29.5" x 6.9" 45.3" x 26.0" x 6.9"

40.6 lbs

+90°

400 x 400mm