# **Public Display**

### LV340C

### **Essential Commercial TV Functionality**

The LG 340C TV has been specifically designed for various business environments. With simple user-friendly interfaces and superb images and video, the LV340C series helps drive messages and images between businesses and their target audiences. Also, the LV340C series supports WOL (Wake on LAN) and SuperSign<sup>™</sup> C , helping management, engineers and IT departments remotely manage and efficiently control the LV340C.



### LV340C

- Public Display Mode
- USB Cloning
- USB Auto Playback +
- RS-232C
- WOL(Wake on LAN)
- Crestron Connected Certification

#### screen size

32" (31.5" Diagonal), 43" (42.5" Diagonal), 49" (48.5" Diagonal), 55" (54.9" Diagonal)



#### Key Features



**Public Display Mode** 

From channel selection to volume level, you can control the TV settings in public areas. Public Display Mode also enables you to restore default settings, as required, on the TVs.



Via the TV's RS-232C port, you can remotely control power and volume settings simultaneously.



WOL (Wake on LAN)

WOL (Wake on LAN) helps you remotely turn on TVs over the internet. Connect TVs and a PC in the same network, and send Magic Packet program to the MAC addresses of registered TVs. Then, it will wake up the TVs via LAN port.

#### Simple & Effective Maintenance



USB Cloning

Clone your LV340C's with efficiency and ease. The USB Cloning feature allows you to simply copy the TV settings to all the LV340C's using a USB memory device (sold separately).

#### Convenience & Entertainment



USB Auto Playback+

Create a media playlist of your choosing (video, music, and/or images) via USB Auto Playback+. Save it to a USB memory device, and then simply connect the USB memory device to the TV to stream your playlist sequentially



Lock Mode

Lock Mode blocks external input signals with non-compliant content. This is a useful feature for preventing misuse of TVs in various facilities or public spaces.



Self Diagnosis

Self Diagnosis enables engineers and IT to engineers to analyze the data and identify technical issues quickly and easily through a USB memory device.



SuperSign<sup>™</sup> C

With SuperSign C, LG's signage management software, you can control and remotely monitor via the LAN port



Welcome Screen (Splash Image)


Display a customized greeting message with your business name/logo on the TV when it is turned on.





## Essential Commercial TV Functionality


#### Dimensions



## Essential Commercial TV Functionality

Specificati	ONS	32	43	49	55
	Diagonal Size	31.5"	42.5"	48.5"	54.9"
DISPLAY	Туре	Direct LED Edge LED			
	Resolution	1,366 x 768 (HD)	58 (HD) 1,920 × 1,080 (FHD)		
	Brightness	240cd/m <sup>2</sup>	240cd/m <sup>2</sup> 400cd/m <sup>2</sup>		
	Viewing Angle Degree	178° / 178°			
	Response Time (G to G)	9			
	Frame Rate	60 Hz			
BROADCASTING SYSTEM	Analog	NTSC			
	Digital	ATSC / VSB / Clear QAM			
VIDEO	Triple XD Engine	•			
	Real Cinema 24p (3:3 Pull down)	•			
	Dynamic Color Enhancer	•			
	Aspect Ratio	6 modes (16:9, Just scan, Set by program, 4:3, Zoom, Cinema Zoom 1)			
AUDIO	Audio Output / Speaker System	5W + 5W / 2.0 ch			
	Sound Mode	6 modes (Standard, News, Music, Cinema, Sport, Game)			
	Optical Sound Sync	•			
	Clear Voice	•			
GENERAL FEATURES	Installation	USB Cloning			
	Management	WOL (Wake On LAN), SNMP, USB Diagnostics, Multi IR Code, HTNG/HDMI-CEC			
	USB	USB Auto playback+, Moving Picture Playback (.asf, wmv, divx, avi, .mp4, .m4y, .moy, .mpg, .mpeg, .mpe, etc.), Picture (jpeg, jpg, jpe, BMP, PNG), Audio Codec (MP3, AAC, M4A, WMA, WMA 10 pro, OGG)			
	Setting Option	Auto Off / Sleep Timer, Smart Energy Saving, Motion Eye Care			
HOSPITALITY FEATURES		PDM (Public Display Mode), Lock Mode, Welcome Screen (Splash Image), Insert Image, External Speaker Ou RJP Compatibility, Crestron® Connected Certified, Time Scheduler			
INTERFACE	Side	HDMI In, USB 2.0			
	Rear	RF In, AV In (Sharing with Component In), Component In + Video, Optical Video Audio Out, HDMI/HDCP In, RGB In, PC Audio Input (Sharing with Component Audio), RS-232C In, RJ45 (SNMP), External Speaker Out			
DIMENSION	Bezel Width (L/R, U, B) : on bezel based (mm)	14.8, 14.8, 17.7	10, 10, 15.2	10, 10, 15.2	12.9, 12.9, 15.9
	Bezel Width (L/R, U, B) : off bezel based (mm)	13, 13, 15.8	8.5, 8.5, 13.7	8.5, 8.5, 13.7	10.4, 10.4, 13.4
	Vesa (mm)	200	200 x 200 300 x 300		k 300
	WxHxD / weight (with stand)	29.1" x 18.6" x 6.6" / 10.8lb	38.3" x 24.6" x 8.7" / 20.5lb	43.6" x 27.6" x 9.3" / 25.2lb	48.9" x 30.5" x 8.5" 36.6lb
	WxHxD / weight (Carton)	32.0" x 20.1" x 5.6" / 13.4lb	41.7" x 26.0" x 6.0" / 24.9lb	47.0" x 30.3" x 6.2" / 29.8lb	53.5" x 32.9" x 6.0" 47.0lb
POWER	Voltage, Hz	100-240V, 50 / 60 Hz			
	Typical (Watts)	16.5	33.0	37.0	49.0
	Stand-by (Watts)	0.5			
STANDARD APPROVAL	Safety	UL			
	Environment	FCC			
	Etc.	RoHS, UL, NOM			
UPC		719192611856	719192611849	719192611832	719192611825

### Connectivity





LG Electronics U.S.A., Inc. HE B2B Division 2000 Millbrook Drive Lincolnshire, IL 60069

All screen images are simulated. Dimensions and weights are approximate. Design, specifications, and features subject to change without notice.

© Copyright 2019 LG Electronics USA, Inc. All rights reserved. LG and the LG logo are registered trademarks of LG Corp.

In Plane Switching is a trademark of LG Philips LCD Ltd. VESA is a trademark of Video Electronics Standards Association. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

http://www.lg.com/us/business/commercial-display

http://www.twitter.com/LGCommDisplays

f http://www.facebook.com/LGcommercialdisplays

http://www.linkedin.com/company/lg-commercial-displays-usa

http://www.youtube.com/lgcommercialdisplayusa

Customer Service: 888.865.3026 www.LG.com/us/commercial/display-support Contact your LG Regional Sales Representative:

Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com

All other product and brand names are trademarks or registered trademarks of their respective companies.

SPEC\_LV340C\_011972\_PR