

27BK750Y

BK750 SERIES

KEY FEATURES

- Full HD IPS Display (1920 x 1080)
- Integrated Power module
- Colour Calibrated
- Reader Mode
- Tilt, swivel, pivot and height adjustment
- Daisy Chain



PRODUCT FEATURES

PANEL

Screen Size	27" (69cm)
Panel Technology	IPS
Aspect Ratio	16:9
Resolution	1920x1080
Brightness	250 cd/m2 (Typ) 200 cd/m2 (Min)
Contrast Ratio	1000:1 (Native)
Response Time	5ms (High) GTG
Viewing Angle (H x V)	178° x 178°
Colour Depth	16.7M colours
Surface Treatment	Anti glare ,3H

CONNECTIVITY

Input (Rear)	Display Port (ver1.2)
Digital	HDMI (ver1.4), DVI
Analogue	
Output (Rear)	USB 3.0 (1 up 4 down, one for quick charging)
Audio	Headphone Out 2 CH Stereo, 1.2W x 2 PC Audio In

ENVIRONMENT CONDITIONS

Operation Temperature	0°C - 40 °C
Operation Humidity	Less than 80 %

ACCESSORIES

Power Cable, Display Port Cable, HDMI Cable

WARRANTY

3 Years (Parts & Labour)

PHYSICAL SPECIFICATIONS

With stand (WxDxH)	612mm x 276mm x 543mm
Without stand (WxDxH)	612mm x 59mm x 368mm
With stand Weight (kg)	7.6 kg
Without stand Weight (kg)	4.9 kg
Carton (WxHxD)	690mm x 531mm x 172mm
Packed Weight (kg)	9.6 kg
VESA™ Standard Mount Interface	100mm x 100mm

STANDARD (CERTIFICATION)

Comparative Energy Consumption	78 kWh / year
Star Rating	6 (Stars)
Active Standby	0.43W
Safety	CB Scheme, RCM
ErP/US EPA	No / Yes (7.0)
EMC	RCM, Class (B)

SPECIAL FEATURES

 Dual Control, Six Axis Control, Super Resolution+, Power Charge
 OSC (On Screen Control / Screen Split), Colour Calibrated & assessment report

Stand

 Tilt -5° (Front) ~ 25° (Rear)
 Swivel (±45°)
 Height Range (150mm)
 Pivot Bi-directional, 90°

POWER

Power Supply	100 ~ 240V, (50/60Hz)
Power Consumption	20.3W (EPA), 28W (typ)
Sleep Model	0.5W
Off Mode	0.003W
Power Type	Built-in



*LED LCD Monitors combine LCD screen with LED back light technology

Disclaimer: All product specifications correct at time of printing. Specifications may change without prior notice.