

34" QHD 21:9 UltraWide™ Curved Monitor UC88 Series



34UC88



## Discover the vibrant beauty LG IPS Monitor 34" QHD 21:9 UltraWide™ Curved Monitor

### FEATURES:

- IPS Panel with QHD(3440x1440)
- Six Axis Control
- Mac Compatible
- 4-Screen Split for multi-tasking
- Reader Mode

\*LED LCD Monitors combine LCD screen with LED back light technology



www.lg.com.au



# Technical Data

## 34UC88



| <b>PANEL</b>                              |  |
|---|--|
| Screen Size                               | 34" (87cm) Curved  |
| Panel Technology                          | IPS  |
| Aspect Ratio                              | 21:9   |
| Native Resolution                         | 3440 x 1440  |
| Brightness                                | 300 cd/m2  |
| Contrast Ratio                            | 1000:1 (Native)  |
| Response Time                             | 14ms (typ), 5m (GTG)   |
| Viewing Angle (H x V)                     | 178° x 178°  |
| Colour Depth                              | 10bits (8bit+FRC), 1.07B   |
| Colour Gamut                              | sRGB over 99%  |
| Surface Treatment                         | Anti - glare, 3H   |
| <b>CONNECTIVITY</b>                       |  |
| Input (Rear)                              | Digital<br>Analogue<br>Audio   |
| External Control                          | USB  |
| Output (Rear)                             | Digital<br>Audio   |
| External Control                          |  |
| <b>PHYSICAL SPECIFICATIONS</b>            |  |
| Set (with stand) Dimension (W x D x H)    | 818mm x 252mm x 568mm (Extended)   |
| Set (without stand) Dimension (W x D x H) | 818mm x 89mm x 361mm   |
| Set (with stand) Weight                   | 8.3kg  |
| Set (without stand) Weight                | 6.2kg  |
| VESA™ Standard Mount Interface            | 100mm x 100mm (VESA compatible)  |
| <b>SPECIAL FEATURES</b>                   |  |
| Additional                                | PIP mode in Screen Split, PBP, DDC/CI, HDCP, Key Lock, Response Time Control, Quick Charge, Freesync (DP 55-75Hz), Game Mode DAS Mode, Black Stabiliser, Smart Energy saving, Automatic standby Reader Mode (Picture Mode), Six Axis Control, Colour Calibrated Dual controller, Screen split 2.0 (OSC), My Display Preset (OSC) OnScreen Control (OSC), Dual EDID (H/W), One Click Stand Set-up |
| <b>ENVIRONMENT CONDITIONS</b>             |  |
| Operation Temperature                     | 0 °C - 40 °C   |
| Operation Humidity                        | Less than 80 %   |
| <b>POWER</b>                              |  |
| Power Supply                              | 100 - 240V, (50/60Hz)  |
| Power Consumption                         | 56.7W(EPA6.0), 65W(typ)  |
| Typical / Smart Energy Saving on          | 1.2W   |
| Power Off                                 | 0.3W   |
| Power Type                                | AC Adapter   |
| <b>STANDARD (CERTIFICATION)</b>           |  |
| Comparative Energy Consumption            | 185.0 (kWh/Year)   |
| Star Rating                               | 3 (Stars)  |
| Active Standby                            | 0.69W  |
| Safety                                    | UL(cUL), TUV-Type  |
| EMC                                       | FCC-B, CE, EPEAT Gold, RCM   |
| ErP/US EPA                                | Yes/ -   |
| <b>ACCESSORIES</b>                        |  |
| Included                                  | HDMI, Power Cord, DisplayPort, Cable holder  |
| Optional                                  |  |
| Warranty                                  | 3 Years (Parts & Labour)   |

Disclaimer: All product specifications are correct at the time of printing. Specifications may change without a prior notice.



