

Model Name			AMNC09GDJR0	
Power Supply		V, Ø, Hz		220-240,1, 50 /60
Power Input	Min./Nom./Max.		W	9 / 18 / 30
Running Current	Min./Nom./Max.		A	0.12 / 0.16 / 0.20
Exterior Color code		-		Munsell 7.5PB 0.2/20 (RAL 9005)
Dimensions	Body	W × H × D	mm	837 × 308 × 192
		W × H × D	inch	32-15/16 × 12-1/8 × 7-9/16
	Shipping	W × H × D	mm	909 × 383 × 256
		W × H × D	inch	35-25/32 × 15-3/32 × 10-3/32
Weight	Body		kg (lbs)	9.2 (20.3)
	Shipping		kg (lbs)	11.2 (24.7)
Heat Exchanger	(Row × Column × Fins per inch) × No.		-	(2 × 23 × 22) × 1
	Face Area		m <sup>2</sup> (ft <sup>2</sup> )	0.20 (2.15)
Fan	Type		-	Cross Flow Fan
	Air Flow Rate	H / M / L	m <sup>3</sup> /min	7.7 / 6.4 / 5.0
		H / M / L	ft <sup>3</sup> /min	272 / 226 / 177
Fan Motor	Type		-	BLDC
	Output		W × No.	30 × 1
Sound Pressure Level		H / M / L	dB(A)	36 / 32 / 27
Sound Power Level		H / M / L	dB(A)	-
Piping Connections	Liquid		mm(inch)	Ø 6.35 (1/4)
	Gas		mm(inch)	Ø 9.52 (3/8)
	Drain	O.D. / I.D.	mm	21.5 / 16.0
Safety Devices			-	Fuse
			-	Thermal Protector for Fan Motor
Connections Method			-	Flared
Power and Communication Cable (included Earth)			No. × mm <sup>2</sup>	4C x 0.75

<b>AMNC12GDJR0</b>	<b>AMNC18GDKR0</b>	<b>AMNC24GDKR0</b>
220-240,1, 50/60	220-240,1, 50 /60	220-240,1, 50/60
9 / 19 / 30	26 / 39 / 60	27 / 45 / 60
0.12 / 0.17 / 0.20	0.22 / 0.28 / 0.40	0.24 / 0.33 / 0.40
Munsell 7.5PB 0.2/20 (RAL 9005)	Munsell 7.5PB 0.2/20 (RAL 9005)	Munsell 7.5PB 0.2/20 (RAL 9005)
837 × 308 × 192	998 x 345 x 212	998 x 345 x 212
32-15/16 × 12-1/8 × 7-9/16	39-9/32 x 13-19/32 x 8-11/32	39-9/32 x 13-19/32 x 8-11/32
909 × 383 × 256	1,080 x 422 x 281	1,080 x 422 x 281
35-25/32 × 15-3/32 × 10-3/32	42-17/32 x 16-5/8 x 11-1/16	42-17/32 x 16-5/8 x 11-1/16
9.2 (20.3)	12.6 (27.8)	13.2 (29.1)
11.2 (24.7)	15.9 (35.1)	16.5 (36.4)
(2 x 23 x 22) x 1	(2×16×20)×1 + (1×8×22)×1	(2×16×20)×1 + (1×8×22)×1
0.20 (2.15)	0.28 (3.01)	0.28 (3.01)
Cross Flow Fan	Cross Flow Fan	Cross Flow Fan
8.1 / 6.7 / 5.3	14.2 / 11.3 / 9.9	15.2 / 12.7 / 10.2
286 / 237 / 187	501 / 399 / 350	537 / 448 / 360
BLDC	BLDC	BLDC
30 × 1	60×1	60×1
38 / 34 / 29	44 / 38 / 34	46 / 41 / 36
-	-	-
Ø 6.35 (1/4)	Ø 6.35 (1/4)	Ø 6.35 (1/4)
Ø 9.52 (3/8)	Ø 12.7 (1/2)	Ø 12.7 (1/2)
21.5 / 16.0	21.5 / 16.0	21.5 / 16.0
Fuse	Fuse	Fuse
Thermal Protector for Fan Motor	Thermal Protector for Fan Motor	Thermal Protector for Fan Motor
Flared	Flared	Flared
4C x 0.75	4C x 0.75	4C x 0.75