


Digital Kiosk for Effective AD and Interior Decor

49KE5E

LG's new floor-standing display, 49KE5E, delivers advertising and information in any type of indoor facility, featuring a sophisticated design and 24/7 flexible operation. Boasting an aluminum hairline finish and robust glass surface, it can reliably withstand external shocks while also blending in with its surroundings.




Digital Kiosk for Effective AD and Interior Decor

49KE5E

Sleek Design

Elegant and Sophisticated Design

Beyond delivering advertising and information, the 49KE5E has value as interior decoration. The minimalist design, including its slim depth, makes it fit any space both physically and aesthetically, and the pure glass surface of its screen adds to the sense of sleek orderliness. In addition, the solid and high-quality aluminum material was given a hairline finish for a smooth surface and a feeling of exclusivity.



Digital Kiosk for Effective AD and Interior Decor

49KE5E

Reliable Operation with High Durability

Protective Glass for Safety

The tempered front glass with shatter-proof film prevents pieces of broken glass from scattering and keeps them attached to the screen. It is the optimum protection for minimizing harm to the user, even in the event of an external impact.



Conventional

49KE5E

Conformal Coating

The product can be often unavoidably exposed to dust and iron powder during maintenance. Conformal coating on major circuit board eliminates such circumstances by protecting it against dust, iron powder, humidity, etc.



Digital Kiosk for Effective AD and Interior Decor

49KE5E

Reliable Operation with High Durability

24/7 Secure Operation

The 49KE5E supports 24/7 operation, which means that owners or managers who run their workplaces can flexibly deploy and operate it free from operational time constraints. LG's continuous verification processes and strict quality standards guarantee stable operation and product quality. As a floor-standing display, it certainly requires no supporting structure or wall-mounting, which makes it an ideal solution for those not wanting to deal with a complicated installation process.



Digital Kiosk for Effective AD and Interior Decor

49KE5E

Easy Content Management

USB Content Playback

There is no need for complex system connections for content playback because the 49KE5E supports USB auto playback and scheduling. A USB can be mounted inside the back cover, preventing it from becoming lost or stolen.

Wi-Fi Connection Ready

Content can also be distributed and managed via wired or wireless network connections. This way, users can set content playback remotely, even from their office.


Space for Media Player

The 49KE5E is not only compatible with media players, but also offers a hidden space for installation. Specialized SIs can flexibly customize and allocate their solutions for optimal use.




Dimension (unit: mm)

49"



Connectivity



- 1 HDMI IN
- 2 DVI-D IN
- 3 LAN
- 4 USB IN 1
- 5 USB IN 2
- 6 IR IN
- 7 AUDIO IN
- 8 AUDIO OUT
- 9 RS232C IN (SVC Only)
- 10 RS232C OUT (SVC Only)
- 11 AC IN



Specifications

49KE5E

PANEL	Screen Size	49"
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness (Typ.)	450 cd/m ² (380 cd/m ² with Protection Glass)
	Contrast Ratio	1,100:1
	Viewing Angle (H x V)	178 x 178
	Color Depth	16.7 Million
	Response Time	12 ms (G to G BW), 10.1 ms (WOT)
	Surface Treatment (Haze)	Hard Coating (3H), Haze 1% (Typ.), Anti-glare Treatment of the Front Polarizer
	Life Time (Typ.)	50,000 Hrs
	Operation Hours	24 Hrs
	Orientation	Portrait
CONNECTIVITY	Input	HDMI, DVI-D, Audio, USB 2.0 (2)
	Output	Audio
	External Control	RS232C In/Out (SVC Only), RJ45 (LAN) In, IR In
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	55.3 mm (T/R/L), 623.9 mm (B) *Portrait Kiosk Scene
	Dimension (W x H x D)	716.6 x 1,855 x 50 mm (The Thickest Part 77 mm) *Without Stand 716.6 x 1,900 x 480 mm *With Stand
	Weight (Head)	45.8 kg
	Weight (Head + Stand)	58.3 kg
	Carton Dimensions (W x H x D)	1,995 x 855 x 265 mm
	Packed Weight	75.5 kg
	VESA™ Standard Mount Interface	N/A
	Glass	4T, Tempered Glass
	SPECIAL FEATURES	Wi-Fi Dongle Ready, Temperature Sensor, USB Auto Playback, Local Contents Scheduling, Fail Over, Image Customization, Lock Mode, Tile Mode Setting (Up to 15x15), Setting Data Cloning (USB), Firmware Update by Network, SNMP (Ver.2), ISM Mode, DPM, Smart Energy Saving, Wake on LAN, HDMI-CEC ¹⁾ (LG Simplelink Only)
ENVIRONMENT CONDITIONS	Operation Temperature	0°C to 40°C
	Operation Humidity	10% to 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
	Power Consumption	Typ. 85 W
		Max. 100 W
		Smart Energy Saving 65 W
CERTIFICATION	Safety	CB/BIS
	EMC	CE (Class A)
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	No
	Media Player Attachable	Yes
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS
	Control and Monitoring Software	SuperSign Control/Control+
ACCESSORIES	Basic	Remote Controller, Power Cord, QSG, Regulation Book, IR Cable
	Optional	Wi-Fi Dongle (AN-WF500)

1) Compatibility may differ by equipment



Download
LG C-Display+
Mobile App

Google Play Store

- www.lg.com/b2b
- www.youtube.com/c/LGCommercialDisplay
- www.facebook.com/LGInformationDisplay
- www.linkedin.com/company/LGInformationDisplay

LG may make changes to specifications and product descriptions without notice.
Copyright © 2018 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.
The names of products and brands mentioned here may be the trademarks of their respective owners.

