

Multiple Screen Split Ultra HD Signage

Ultra HD Large Display, 75UH5PC



The new Ultra HD large display, 75UH5PC supports displaying Ultra HD content as well as a divided content layout to show up to 4 split images on one screen. Its benefit enables you to create various formats of content to deliver commercial message effectively. Also, it is enhanced in content management. With LG SuperSign providing basic content templates, you can create and edit content simply and quickly on your mobile device or signage display.



Key Features

Ultra HD



Ultra HD Resolution (3,840 x 2,160)

Ultra HD Large screen delivers immersive viewing experience by 4 times higher definition picture quality than FHD.



High Efficiency Video Coding

Supports HEVC-based content which has the double data compression ratio than the H.264, so network traffic can be reduced by half.




Multiple Screen



Multiple Screen with PBP or PIP

PBP (Picture-By-Picture) and PIP (Picture-In-Picture) feature gives a chance to compose up to 4 divided split screen on landscape or portrait display format.



Download LG Commercial Display Mobile App



Learn more www.lg.com/b2b

YouTube youtube.com/c/LGCommercialDisplay

LG may make changes to specifications and product descriptions without notice.
Copyright © 2017 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.
The names of products and brands mentioned here may be the trademarks of their respective owners.



Multiple Screen Split Ultra HD Signage

Ultra HD Large Display, 75UH5PC



Screen Sizes
75"

75UH5PC

- Brightness : 500cd/m²
- Bezel : 14.9 mm (Off-bezel)
- Depth : 59.5 mm (Without Handle)
- Interface : DP / HDMI / DVI / RS232C / RJ45 / Pixel Sensor / SD Card / USB
- SuperSign W/C



Other Features

Smart Platform



Quad Core SoC*

The High Performance SoC can execute several tasks at the same time and provides smooth content playback.



*SoC : System-on-Chip

webOS 2.0

The webOS 2.0 platform provides powerful and convenient tools to create, including app development materials.



Supportive Convenience

BEACON

With BEACON and Bluetooth Low Energy (BLE) supported by 75UH5PC, retail stores can provide coupons and information in real-time.



OPS* Kit / HDBaseT Box

The 75UH5PC provides an OPS Kit to connect a third-party OPS player or HDBaseT box. Users have the flexibility to choose any media player as long as it complies with the OPS.




*OPS : Open Pluggable Specification

Easy Maintenance




Real-Time Remote Monitoring

When an alarm occurs, an e-mail notification is sent using SuperSign C or SI SW through the SNMP Protocol. In case of malfunctions or errors, real-time remote care is available.



Easy Management by SuperSign

You can easily create, schedule and distribute the contents you want with various templates provided by SuperSign™ W.



Specifications

	75UH5PC
PANEL	Screen Size: 75" Panel Technology: IPS Aspect Ratio: 16:9 Native Resolution: 3,840 x 2,160 (UHD) Brightness: 500cd/m ² Contrast Ratio: 1,200:1 Dynamic CR: 4,000,000:1 (DTV Label only) Viewing Angle (H x V): 178 x 178 Response Time: 6ms (G to G) Surface Treatment: Low Haze 3% Life Time (Min.): 50,000 Hrs Operation Hours: 24 Hrs Orientation: Portrait & Landscape
CONNECTIVITY	Input: HDMI (3), DP, DVI-D, Audio, USB 3.0, SD Card Output: DP, Audio External Control: RS232C, RJ45, IR Receiver, Pixel Sensor
PHYSICAL SPECIFICATION	Bezel Color: Black Bezel Width: 14.9 mm (Off-bezel) Monitor Dimension (W x H x D): 1,682.4 x 963.3 x 59.5 mm (Without Handle, with LG logo) Weight (Head): 41.5kg Carton Dimensions (W x H x D): 1,816 x 1,123 x 228mm Packed Weight: 49 kg VESA™ Standard Mount Interface: 600 x 400mm
SPECIAL FEATURES	Temperature Sensor, Auto Brightness Sensor, Tile Mode (up to 15x15), Natural Mode@Tile Mode, ISM Method, Internal Memory (8GB, System 4GB), Wi-Fi built-in (802.11n), USB Cloning, Content Scheduling, Sync mode, PM mode, Fail Over, Wake on LAN, BEACON (On/Off), Embedded Template, PIP/PBP (2/3/4)
ENVIRONMENT CONDITIONS	Operation Temperature Range: 0 °C to 40 °C Operation Humidity Range: 10 % to 80 %
POWER	Power Supply: 100-240V~, 50/60Hz Power Type: Built-in Power Power Typ.: 160 W Consumption Smart Energy Saving: 120 W
STANDARD (CERTIFICATION)	Safety: UL / cUL / CB / TUV / KC EMC: FCC Class "A" / CE / KCC ErP / Energy Star: No / Energy Star 7.0
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible: Yes External Media Player Attachable: Yes (MP500 / MP700)
SOFTWARE COMPATIBILITY	Content Management Software: SuperSign W Control and Monitoring Software: SuperSign C
ACCESSORY	Basic: Remote Controller (include 2ea batteries), Power Cord, QSG, DP 1.8M, Regulation Book, Phone to RS232C Gender, Memory Cover Optional: Pixel Sensor (KT-SPO), Media Player, OPS Kit (KT-OPSA), HDBaseT (EB-B100), LSW640A/B (Wall Mount)


Dimension (unit : mm)

75"

1,682.4 x 963.3* x 59.5* mm / 41.5 kg (Without handle)

1,682.4 x 963.3* x 73.9* mm (With handle)

* With LG logo



Connectivity

- LAN
- AUDIO IN
- AUDIO OUT
- DP OUT
- DVI-D IN
- PIXEL SENSOR
- IR & LIGHT SENSOR
- DP IN
- HDMI IN 3
- HDMI IN 2
- HDMI IN 1
- USB 3.0 IN
- SD CARD
- RS-232C IN
- RS-232C OUT

