

Draw Attention to Windows

# VIVID TRANSPARENT DISPLAY 26TS30MF

26TS30MF



## HIGH VISIBILITY

### SUPERIOR COLOR GAMUT

With Superior Color Gamut, TS Series presents more clearer image.



Conventional

VS



TS Series

## TRUE COLOR (IPS)

LG IPS technology provides true vivid color than conventional display.



Conventional

VS



TS Series

## EASY CUSTOMIZATION OPEN FRAME

TS Series fits to any customer need and circumstance with its open frame. It can be designed according to customer request at an affordable price.

# VIVID TRANSPARENT DISPLAY 26TS30MF



26TS30MF

## FEATURES

- LED (TV Panel)
- 1,366 x 768 (HD)
- High Contrast Ratio : 1,000(Typ)
- Transmittance : 4.84%(Typ)
- Color Gamut : 68%
- Bezel : 71.5mm (T), 15.6mm (B/L/R)
- Easy Customization (Open Frame)
- \* Kiosks not provided by LGE

## SPECIFICATIONS

|              |                       | 26TS30MF                             |  |                        |                                    |  |                       |
|--------------|-----------------------|--------------------------------------|--|------------------------|------------------------------------|--|-----------------------|
| PANEL        | Screen Size           | 26" Class (26.01" measured diagonal) |  | PHYSICAL SPECIFICATION | Bezel Width                        | 71.5mm (Top), 15.6mm (Bottom / Left / Right) |                       |
|              | Panel Technology      | IPS                                  |  |                        | Monitor Dimension (W x H x D)      | 60.95cm x 41.33cm x 0.88cm                   |                       |
|              | Aspect Ratio          | 16 : 9                               |  |                        | Weight (head)                      | 1.62kg                                       |                       |
|              | Native Resolution     | 1,366 x 768 (HD)                     |  |                        | Carton Dimensions (W x H x D)      | 76.0cm x 63.5cm x 57.0cm                     |                       |
|              | Transmittance         | 4.84% (Typ)                          |  |                        | Packed Weight                      | 24.6kg                                       |                       |
|              | Contrast Ratio        | 1,000 (Typ)                          |  |                        | VESA™ Standard Mount Interface     | N/A  |                       |
|              | Dynamic CR            | N/A                                  |  |                        | SPECIAL FEATURES                   | Additional                                   | Color Gamut (68%)     |
|              | Viewing Angle (H x V) | 178 x 178                            |  |                        |                                    | ENVIRONMENT CONDITIONS                       | Operation Temperature |
|              | Response Time         | 8ms (G to G, *WOT)                   |  |                        | Operation Humidity                 |  | 10% ~ 80%             |
| CONNECTIVITY | Input (Rear)          |                                      |  | POWER                  | Power Supply                       |  | N/A                   |
|              | Digital               | LVDS(1)                              |  |                        | Power Consumption                  |  |                       |
|              | Analog                | N/A                                  |  |                        | Typical / Smart Energy Saving (on) | 2.7W (12V Input)                             |                       |
|              | Audio                 | N/A                                  |  |                        | DPMS                               | N/A  |                       |
|              | External Control      | N/A                                  |  |                        | Power Off                          | N/A  |                       |
|              | USB                   | N/A                                  |  |                        |                                    |  |                       |

\* WOT : Within Operation Temperature  
 ※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

## DIMENSION (unit : mm)

