

Specifications

SE3DD Series		55SE3DD	49SE3DD	43SE3DD
PANEL	Screen Size	55"	49"	43"
	Panel Technology	IPS		
	Aspect Ratio	16:9		
	Native Resolution	1,920 x 1,080 (FHD)		
	Brightness	300 cd/m²		
	Contrast Ratio	1,000:1 (Typ.)		
	Dynamic CR	500,000:1		
	Viewing Angle (H x V)	178 x 178		
	Response Time	12 ms (G to G BW), 9.0 ms (WOT)	12ms (G to G BW), 10.1 ms (WOT)	12ms (G to G BW), 9.4 ms (WOT)
	Surface Treatment	Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 1% (Typ.))		
CONNECTIVITY	Guaranteed Operating Hours	16 Hrs		
	Orientation	Landscape & Portrait		
	Input	HDMI (2), Analog (RGB), Audio, USB		
	Output	External Speaker Out		
	External Control	RS232C (In/Out), RJ45, IR Receiver		
PHYSICAL SPECIFICATION	Bezel Color	Black		
	Bezel Width	11.9 mm (T/R/L), 18 mm (B)		
	Monitor Dimension (W x H x D)	1,238 x 714.9 x 38.6 mm	1,102.2 x 638.5 x 38.6 mm	969.6 x 563.9 x 38.6 mm
	Weight (Head)	17.1 kg	13.9 kg	9.6 kg
	Monitor with Optional Stand & Speaker Dimensions (W x H x D)	1,238 x 773.4 x 219.6 mm	1,102.2 x 696.8 x 219.6 mm	969.6 x 622.2 x 193 mm
	Weight (Head+Stand+Speaker)	19.9 kg	17.7 kg	12.6 kg
	Carton Dimensions (W x H x D)	1,330 x 807 x 170 mm	1,197 x 760 x 166 mm	1,052 x 650 x 123 mm
	Packed Weight	21.3 kg	17.0 kg	12.2 kg
SPECIAL FEATURES	VESA™ Standard Mount Interface	300 x 300 mm	300 x 300 mm	200 x 200 mm
		Temperature Sensor, Tile Mode (Up to 15x15), Natural Mode@Tile Mode, DPM Select, DPM Wake Up, ISM Method, Energy Saving, Smart Energy Saving, USB Content Scheduling, Conformal Coating, SNMP Support, Wi-Fi Ready (Dongle), No Signal Image setting, Holiday Schedule/Local Time Auto Setting, Fail over, Wake on LAN		
ENVIRONMENTAL CONDITIONS	Operating Temperature Range	0 °C to 40 °C		
	Operating Humidity Range	10 % to 80 %		
POWER	Power Supply	100-240V~, 50/60Hz		
	Power Type	Built-In Power		
POWER CONSUMPTION	Typ.	80 W	65 W	55 W
	Smart Energy Saving	55 W	50 W	45 W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC		
	EMC	FCC Class "A" / CE / KCC		
	ErP / Energy Star	Yes / Yes (Energy Star 7.0)		
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	No		
	External Media Player Attachable	Yes (MP500/MP700)		
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign W	SuperSign W	SuperSign W
	Control and Monitoring Software	SuperSign C	SuperSign C	SuperSign C
ACCESSORIES	Basic	Remote Controller (include battery Zea), Power Cord, QSG, RGB Cable, Regulation Book, IR Receiver		
		Speaker (SP-5000), Stand (ST-492T), Media Player (MP500/MP700), Wall Bracket (LSW350B), VESA Adapter (AM-B330S), Wi-Fi Dongle (AN-WF500), Touch Overlay (KT-T550)	Speaker (SP-5000), Stand (ST-492T), Media Player (MP500/MP700), Wall Bracket (LSW350B), VESA Adapter (AM-B330S), Wi-Fi Dongle (AN-WF500), Touch Overlay (KT-T490)	Speaker (SP-5000), Stand (ST-432T), Media Player (MP500/MP700), Wall Bracket (LSW230B), VESA Adapter (AM-B220S), Wi-Fi Dongle (AN-WF500), Touch Overlay (KT-T430)
	Optional			

Simple Way to Manage Your Digital Signage  
Standard Essential SE3DD Series



Simplify promotion content or sales information management with the LG SE3DD Series that satisfies a wide range of display purposes in your business. This series has a practical design with a slim bezel and depth for optimum space utilization. Multiple screen sizes ensure the best selection for your business environment.


Key Features

Sleek Design




Slim Bezel & Depth

The thin bezel & depth allows a perfect fit for a sleek look.



Detachable Logo

Portrait mode allows the logo to be positioned in the desired setting.



Cable Management

The well-organized cable terminals in the back optimize available space.



Connectivity

- 1

SPEAKER OUT
- 2

AUDIO IN
- 3

LAN
- 4

RGB IN
- 5

IR IN
- 6

RS232C IN
- 7


RS232C OUT
- 8

HDMI 1
- 9

HDMI 2
- 10

USB

55SE3DD / 49SE3DD / 43SE3DD



Download LG Commercial Display Mobile App



Learn more [www.lg.com/b2b](http://www.lg.com/b2b)  
**You Tube** [youtube.com/c/LGECCommercialDisplay](https://youtube.com/c/LGECCommercialDisplay)

LG may make changes to specifications and product descriptions without notice.  
Copyright © 2017 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.  
The names of products and brands mentioned here may be the trademarks of their respective owners.



USB Content Management



USB Content Scheduling

Play and schedule contents with a USB connection-no server connection required.



\*Supported Content Type: Video (MPEG1/2/4, H.264), Audio (MP3, AC3, MPEG, AAC, HEAAC, LPCM), Image (JPEG, PNG, BMP)

Dust & Humidity Protection



Conformal Coating

Circuit board reliability is enhanced with conformal coating that protects against dust, iron powder, humidity and other harsh conditions.





## Standard Essential SE3DD Series



55", 49", 43"


- Edge LED
- Brightness: 300 cd/m<sup>2</sup>
- Bezel: T/L/R 11.9 mm, B 18.0 mm
- Depth: 38.6 mm
- Interface: HDMI (2), RGB, RJ45, IR, RS232C, USB

### Convenient Management

Through its diverse interface, the signage lets you connect more than one device for optimal use.



In case a media player is disconnected, it is possible to play back the image preset by users using USB instead of the no signal image.



Technical drawing of the LG 24MP23PE monitor showing dimensions and internal components. The drawing includes the following dimensions:

- Top width: 384.76
- Top center width: 200
- Top right width: 384.8
- Left height: 170.2
- Bottom left height: 200
- Bottom left height: 193.7

The drawing also shows the internal components, including the LG logo, a speaker, and various ports and connectors.