LG UHD Signage Provides Information Effectively

The UH7F series is a UHD signage that has been optimized for various indoor environments. It features superior UHD quality, slim design, external dust protection, and various convenience for users.



Superb Picture Quality



Sleek and Practical Design




Product Reliability




Easy Installation






ULTRA HD Resolution

With the resolution that is 4 times higher than FHD, it makes the color and details of the contents more vivid and realistic. In addition, the wide viewing angle applied with LG IPS Panel, provides clear contents with no distortion.



High Efficiency Video Coding

The UH7F series supports HEVC* which efficiently compresses/ decompresses high-capacity UHD contents, playing ultra-high quality videos with half the network traffic when compared to the existing H.264 codec.



* HEVC: High Efficiency Video Coding

Narrow Bezel & Slim Depth

The UH7F series has a smaller bezel size and thickness, which saves space and enables easy installation. In addition, it increases the immersive experience from the screen and provides a sophisticated design, improving the décor of the space where the product is installed.



Detachable Logo and Built-in Speaker

The UH7F series is equipped with a new transparent logo which is well organized with surroundings. Also, its removable feature gives users flexibility for installation. Contents will be enriched with sound effects from built-in speakers, without the need for purchasing or installing external speakers.



IP5x Certified Design

The IP5x Dust-Proof Certification ensures that the product is completely protected from dust, eliminating the risk of performance degradation.

30° Tilting Installation

The UH7F series supports 30-degree installation* when placed at a high area, in consideration of the user's comfort for viewing.





^{*} Only supports the landscape installation


Auto Screen Rotation

The UH7F series automatically detects its orientation (landscape or portrait mode) in the initial installation step, so manual rotation set-up process isn't required. The direction of OSD and background contents will be already set when you turn on a display at first.



Fine Adjustment

The UH7F series is equipped with a "horizontal sensor" which shows users how the device is tilt, so that it can be precisely installed.



Remote Monitoring

The UH7F series can email notifications to users when there is a problem, such as tilting of the product by external impact, so users can operate the product in a safer manner as they can get the information about the problem right away.



Simple Accessibility

Unlike previous models where various buttons have to be pressed for control, the UH7F series provides a single joystick to easily facilitate power on/off, input/setting operation, volume control, etc.



High-Performance with webOS

Built-in Quad Core SoC can execute several tasks at once while providing smooth content playback without the need for a media player. Also LG webOS platform enhances user convenience with intuitive GUI and simple app development tools.



Various Sensor Applications

LG webOS smart signage platform easily supports connections with external sensors such as GPIO, NFC/RFID, temperature sensors, etc, via USB plug-in. The overall cost for maintenance is reduced as there's no need to purchase additional software or media players for creating value-added solutions.



SMART FUNCTION

UHD Signage UH7F Series

Compatibility with AV Control System

The UH7F series has been certified Crestron Connected® for high compatibility with professional AV controls to achieve seamless integration and automated control*, boosting business management efficiency.




* Network based control

Compatibility with Video Conference System


For the optimum visual meeting, the UH7F series has certified its compatibility with Cisco System that offers powerful and integrated control* for a smarter video conference, eliminating a waste of time for setting up the picture quality or changing input on incoming calls.



^{*} Using an HDMI cable connection



CONNECTIVITY



Panel Connectivity	Screen Size Panel Technology Aspect Ratio Native Resolution Brightness (Typ.) Contrast Ratio Viewing Angle (H x V) Response Time Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color Bezel Worlth		65° IPS 16:9 3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape	55" IPS 16:9 3,840 × 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 × 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	49° IPS 16:9 3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape		
	Aspect Ratio Native Resolution Brightness (Typ.) Contrast Ratio Viewing Angle (H x V) Response Time Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color		16:9 3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs	16:9 3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	16:9 3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs		
	Native Resolution Brightness (Typ.) Contrast Ratio Viewing Angle (H x V) Response Time Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color		3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs	3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	3,840 x 2,160 (UHD, RGB) 700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs		
	Brightness (Typ.) Contrast Ratio Viewing Angle (H x V) Response Time Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color		700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs	700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	700 cd/m² 1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs		
	Contrast Ratio Viewing Angle (H x V) Response Time Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color		1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs	1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	1,100:1 178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs		
	Viewing Angle (H x V) Response Time Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color		178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs	178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	178 x 178 8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs		
	Response Time Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color		8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs	8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	8ms (G to G) Haze 3% 50,000 Hrs 24 Hrs		
Connectivity	Surface Treatment (H Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color	aze)	Haze 3% 50,000 Hrs 24 Hrs	Haze 3% 50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	Haze 3% 50,000 Hrs 24 Hrs		
Connectivity	Life Time (Typ.) Operation Hours Orientation Input Output External Control Bezel Color	aze)	50,000 Hrs 24 Hrs	50,000 Hrs 24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	50,000 Hrs 24 Hrs		
Connectivity	Operation Hours Orientation Input Output External Control Bezel Color		24 Hrs	24 Hrs Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0	24 Hrs		
Connectivity	Orientation Input Output External Control Bezel Color			Portrait & Landscape HDMI (3), DP, DVI-D, Audio, USB 2.0			
Connectivity	Input Output External Control Bezel Color		Portrait & Landscape	HDMI (3), DP, DVI-D, Audio, USB 2.0	Portrait & Landscape		
Connectivity	Output External Control Bezel Color				,		
Connectivity	External Control Bezel Color				HDMI (3), DP, DVI-D, Audio, USB 2.0		
	Bezel Color		DP, Audio (Off/Fixed/Variable),				
			RS232C in/Out, RJ45 (LAN) jn, iR in				
	Bezel Width		Black	Black	Black		
	Bezel Width		9.9mm(T/R/L), 14.4mm(B)	9.9mm(T/R/L), 14.4mm(B)	9.9mm(T/R/L), 14.4mm(B)		
	Monitor Dimension (W x H x D)		1,453.3mm x 844mm x 39.9mm	1,234.4mm x 720.9mm x 39.9mm	1,098.6mm x 644.5mm x 39.9mm		
Mechanical	Weight (Head)		28.2 kg	18.9 kg	15.4 kg		
Specification	Carton Dimensions (W x H x D)		1,600mm x 970mm x175mm	1,360mm x 810mm x 175mm	1,197mm x 740mm x 162mm		
	Packed Weight		32.5 kg	23.4 kg	18 kg		
	Handle		No	No	No		
	VESA [™] Standard Mount Interface		300 x 300	300 x 300	300 x 300		
Key Feature	Internal Memory 8GB (System 4GB + Available 3.6GB), Built-in Wi-Fi, Built-in Speaker, Temperature Sensor, Auto Brightness Sensor, Acceleration Sensor, Local Key Operation, Embedded CMS (USB Auto Playback, Local Contents Scheduling, Group Manager), Fail over, Image Customization (Booting Logo, No Signal), Content Sync (RS232C, Local Network), PIP/PBP(4), Screen Share, Video Tag(4), Play via URL, OSD Rotation, Tile Mode Setting (Max. 15 x 15), Setting Data Cloning, Firmware Update by Network, SNMP 2.0, ISM Mode, Crestron Connected ⁸⁰¹ , DPM, Smart Energy Saving, Wake on LAN, Beacon, HDMI-CEC ²¹ , SI Server Setting						
6 115 1	Tilt (Max)		+30°	+30°	+30°		
Special Feature	IP Rating		IP5x	IP5x	IP5x		
Environmental	Operation Temperature		0°C to 40°C	0°C to 40°C	0°C to 40°C		
Conditions	Operation Humidity		10% to 80%	10% to 80%	10% to 80%		
	Power Supply		100-240V-, 50/60Hz	100-240V-, 50/60Hz	100-240V-, 50/60Hz		
	Power Type		Built-In Power	Built-In Power	Built-In Power		
Power	Power	Typ. / Max.	130W / 180W	110W / 160W	100W / 145W		
	Consumption	Smart Enegy Saving	100W	85W	75W		
	Safety		IEC 60950-1 / EN 60950-1 / UL 60950-1	IEC 60950-1 / EN 60950-1 / UL 60950-1	IEC 60950-1 / EN 60950-1 / UL 60950-		
Certification	EMC		FCC Class "A" / CE / KC	FCC Class "A" / CE / KC	FCC Class "A" / CE / KC		
	ErP / Energy Star		Yes / Yes (Energy Star 7.0)	Yes / Yes (Energy Star 7.0)	Yes / Yes (Energy Star 7.0)		
Media player	OPS Type Compatible		Yes	Yes	Yes		
Compatibility	External Media Player Attachable		Yes	Yes	Yes		
	Content Management Software		SuperSign CMS	SuperSign CMS	SuperSign CMS		
Software	Control and Monitoring Software		SuperSign Control/Control+	SuperSign Control/Control+	SuperSign Control/Control+		
Compatibility	Signage365Care		Yes	Yes	Yes		
Accessories	Basic		Remote Controller, Power Cord, QSG, HDMI Cable, Regulation Book, Phone to RS232C Gender				

1) Network based control 2) Compatibility may differ by equipment









