

CEILING CONCEALED DUCT

STANDARD INVERTER (R410A)

MID / HIGH STATIC PRESSURE
- CM18 / CM24 / UM30



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
:www.eurovent-certification.com

UU18W



UU24W
UU30W



INDOOR				CM18 N14	CM24 N14	UM30 N14
Capacity	Cooling	Min / Nom / Max	kW	1.8 / 5.0 / 6.0	2.8 / 6.8 / 7.5	3.2 / 7.8 / 8.8
	Heating	Min / Nom / Max	kW	2.2 / 6.0 / 7.2	3.2 / 7.5 / 8.3	3.6 / 9.0 / 9.9
Low Temperature Capacity	Heating -7°C	Max	kW	5.4	7.2	8.1
			Power Input (Set)	Cooling	Nom	kW
Power Input (Set)	Heating	Nom	kW	1.66	2.34	2.62
			Power Input (Indoor)	Min / Max (Nom ESP)	W	90 / 160
Running Current	Cooling / Heating	Nom	A	6.5 / 7.6	9.1 / 10.3	10.1 / 10.7
Power Supply	Ø / V / Hz			1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.41	3.11	3.51
COP				3.61	3.21	3.70
SEER				6.10	6.10	6.10
SCOP				4.25	3.90	4.00
Pdesign (@ -10°C)	kW			4.1	6.0	6.5
Seasonal Energy Label	Cooling / Heating (A++ to E Scale)			A++ / A+	A++ / A	A++ / A+
Annual Energy Consumption	Cooling / Heating		kWh	287 / 1,383	390 / 2,154	448 / 2,275
	Liquid		mm (inch)	Ø6.35 (1/4)	Ø9.52 (3/8)	Ø9.52 (3/8)
Piping Connection	Gas		mm (inch)	Ø12.7 (1/2)	Ø15.88 (5/8)	Ø15.88 (5/8)
	Drain	O.D. / I.D.	mm	32 / 25	32 / 25	32 / 25
	Air Flow Rate	High / Medium / Low	m³/min	16.5 / 14.5 / 13.0	18.0 / 16.5 / 14.5	22.0 / 20.0 / 18.0
Sound Pressure	Cooling	High / Medium / Low	dBA	34 / 32 / 30	35 / 34 / 32	37 / 35 / 34
Sound Power	Cooling	Max	dBA	59	60	62
Dehumidification Rate	l/h			2.0	2.5	2.8
Dimensions	Body	W x H x D	mm	900 x 270 x 700	900 x 270 x 700	900 x 270 x 700
Net Weight	Body		kg	23.8	24.2	25.3
External Static Pressure	Min - Max			mmAq (Pa)	2.5-15 (25-147)	2.5-15 (25-147)

OUTDOOR				UU18W UE4	UU24W U44	UU30W U44
Compressor	Type			Twin Rotary	Twin Rotary	Twin Rotary
Airflow Rate	Nom	m³/min		50	58	58
Sound Pressure	Cooling	Nom	dBA	47	48	48
	Heating	Nom	dBA	52	52	52
Sound Power	Cooling	Max	dBA	63	67	68
Dimensions	W x H x D			mm	870 x 655 x 320	950 x 834 x 330
Net Weight				kg	44.6	56.1
Refrigerant	Type			-	R410A	R410A
	Charge	g		1,300	2,000	2,000
	Additional Charge	g/m		20	40	40
	GWP			-	2087.5	2087.5
	TCO2eq			-	2.7	4.2
Operation Range (Outdoor)	Cooling	Min - Max	°C DB	-15 - 48	-15 - 48	-15 - 48
	Heating	Min - Max	°C WB	-18 - 18	-18 - 18	-18 - 18
Power Supply	Ø / V / Hz			1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm²			3C x 2.5	3C x 2.5	3C x 2.5
Transmission Cable	No. x mm²			4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker	A			20	25	25
Piping Length Total	Min - Max			m	5 - 30	5 - 50
Piping Elevation Difference	IDU - ODU	Max	m	30	30	30
Piping Connection	Liquid		mm (inch)	Ø6.35 (1/4)	Ø9.52 (3/8)	Ø9.52 (3/8)
	Gas		mm (inch)	Ø12.7 (1/2)	Ø15.88 (5/8)	Ø15.88 (5/8)

Note : 1. Due to our policy of innovation some specifications may be changed without notification.
2. Definition of Power Input Nominal conditions - Performance tested under EN14511
3. Capacities are based on the following conditions:
Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB
4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition
5. This product contains fluorinated greenhouse gases (R410A)

STANDARD INVERTER (R410A)

MID / HIGH STATIC PRESSURE
- UM36 / UM42 / UM48 / UM60



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
:www.eurovent-certification.com

UU36W



UU42W
UU48W
UU60W



INDOOR				UM36 N24	UM42 N24	UM48 N34	UM60 N34
Capacity	Cooling	Min / Nom / Max	kW	4.0 / 10.0 / 11.0	5.0 / 12.1 / 13.2	5.6 / 14.0 / 15.4	5.9 / 14.8 / 16.3
	Heating	Min / Nom / Max	kW	4.5 / 11.2 / 12.3	5.6 / 14.0 / 15.0	6.6 / 15.8 / 18.2	6.8 / 16.8 / 18.7
Low Temperature Capacity	Heating -7°C	Max	kW	10.0	12.5	14.8	15.2
			Power Input (Set)	Cooling	Nom	kW	3.12
Power Input (Set)	Heating	Nom	kW	3.19	3.86	4.39	4.79
			Power Input (Indoor)	Min / Max (Nom ESP)	W	200 / 360	230 / 380
Running Current	Cooling / Heating	Nom	A	13.6 / 13.9	16.6 / 17.2	17.3 / 18.5	19.1 / 20.2
Power Supply	Ø / V / Hz			1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.21	3.22	3.41	3.31
COP				3.51	3.63	3.60	3.51
SEER				5.11	5.10	5.20	5.10
SCOP				3.81	3.58	3.65	3.65
Pdesign (@ -10°C)	kW			7.8	11.5	12.0	12.0
Seasonal Energy Label	Cooling / Heating			A / A (A++ to E Scale)	-	-	-
Annual Energy Consumption	Cooling / Heating		kWh	685 / 2,866	-	-	-
	Liquid		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)
Piping Connection	Gas		mm (inch)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)
	Drain	O.D. / I.D.	mm	32 / 25	32 / 25	32 / 25	32 / 25
	Air Flow Rate	High / Medium / Low	m³/min	32.0 / 28.0 / 24.0	38.0 / 33.0 / 28.0	40.0 / 34.0 / 28.0	50.0 / 45.0 / 40.0
Sound Pressure	Cooling	High / Medium / Low	dBA	36 / 34 / 33	38 / 36 / 34	40 / 38 / 36	42 / 40 / 38
Sound Power	Cooling	Max	dBA	60	62	65	66
Dehumidification Rate	l/h			3.2	3.6	4.5	5.0
Dimensions	Body	W x H x D	mm	1,250 x 270 x 700	1,250 x 270 x 700	1,250 x 360 x 700	1,250 x 360 x 700
Net Weight	Body		kg	35.0	37.0	42.5	42.5
External Static Pressure	Min - Max			mmAq (Pa)	4-15 (39-147)	5-15 (49-147)	5-15 (49-147)

OUTDOOR				UU36W U02	UU42W U32	UU48W U32	UU60W U32
Compressor	Type			Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary
Airflow Rate	Nom	m³/min		90	110	110	110
Sound Pressure	Cooling	Nom	dBA	53	52	52	52
	Heating	Nom	dBA	54	54	54	54
Sound Power	Cooling	Max	dBA	66	67	68	71
Dimensions	W x H x D			mm	950 x 1,170 x 330	950 x 1,380 x 330	950 x 1,380 x 330
Net Weight				kg	81.0	92.0	92.0
Refrigerant	Type			-	R410A	R410A	R410A
	Charge	g		2,800	3,400	3,400	3,400
	Additional Charge	g/m		40	40	40	40
	GWP			-	2087.5	2087.5	2087.5
	TCO2eq			-	5.8	7.1	7.1
Operation Range (Outdoor)	Cooling	Min - Max	°C DB	-15 - 48	-15 - 48	-15 - 48	-15 - 48
	Heating	Min - Max	°C WB	-18 - 18	-18 - 18	-18 - 18	-18 - 18
Power Supply	Ø / V / Hz			1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable	No. x mm²			3C x 5.0	3C x 5.0	3C x 5.0	3C x 5.0
Transmission Cable	No. x mm²			4C x 0.75	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker	A			40	40	40	40
Piping Length Total	Min - Max			m	5 - 50	5 - 75	5 - 75
Piping Elevation Difference	IDU - ODU	Max	m	30	30	30	30
Piping Connection	Liquid		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)	Ø9.52 (3/8)
	Gas		mm (inch)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)	Ø15.88 (5/8)

Note : 1. Due to our policy of innovation some specifications may be changed without notification.
2. Definition of Power Input Nominal conditions - Performance tested under EN14511
3. Capacities are based on the following conditions:
Cooling : - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB Heating : - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB
4. Annual energy consumption : based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition
5. This product contains fluorinated greenhouse gases (R410A)