

# 1. Specification

\*This file is base on v1.10.4 of AC Ez Touch



**AC Ez Touch**

Model no.	PACEZA000
Dimension (WxHxD)	137mm x 121mm x 25mm
Weight (kg)	0.66 kg (Gross:1.618kg)
Max. number of unit	64
Applicable unit type	Air conditioner, ERV, DX ERV, Hydro kit (Heating)
Display	5 inch color LCD Screen (800*480)
Power	12VDC (3.33A), 24VAC
Surrounding Conditions	Operating Temperature : 0~40°C Storage Temperature : -20~60°C Humidity : 0~98% (non-condensing)
LG Comm. type	1 Channel RS485 *Channel 1 : Outdoor unit, PI485GW
Ethernet	100Mbps
External Interface	1 Digital Input, 1 Analog Input

## Features

### Standard Features

- Indoor Unit Control/Monitoring by Groups/Indoor Units
- Web Access with Graphical User Access Control
- Total 200 Schedule Events  
: Weekly, Monthly, Exception day setting
- 1 Digital Input
- Multiple Language Selections  
(Eng, Ita, Spa, Por, Rus, Fra, Ger, Tur, Pol, Chi, Kor)
- Max.5,000 error history (1 year)
- Max.5,000 alarm history (1 year)

### Advanced Function

- Two Set point Auto-changeover / Setback
- Temperature Set point Range Limit
- Remote Controller Lock (All, Temp, Mode, Fan Speed)
- Energy save mode
- Change alarm: Oil change / Filter change
- Energy Management with PDI (prediction, saving)  
: today / week / month (max. 4month)

### Optional Accessories

- PDI(Power Distribution Indicator) - PQNUD1S40  
PPWRDB000