

Type			Fresh Air Intake Unit	
Model		Unit	ARNU76GB8Z4	ARNU96GB8Z4
Cooling Capacity		kW	22.4	28.0
		kcal/h	19,300	24,100
		Btu/h	76,400	95,900
Heating Capacity		kW	21.4	26.7
		kcal/h	18,410	23,000
		Btu/h	73,080	91,360
Power Input (H / M / L)		W	230 / 200 / 200	360 / 230 / 230
Casing			Galvanized Steel Plate	Galvanized Steel Plate
Dimensions (WxHxD)	Body	mm	1,562 x 460 x 688	1,562 x 460 x 688
		inch	61-1/2 x 18-1/8 x 27-3/32	61-1/2 x 18-1/8 x 27-3/32
Coil	Rows x Columns x FPI		3 x 20 x 19	3 x 20 x 19
	Face Area	m²	0.59	0.59
Fan	Type		Sirocco Fan	Sirocco Fan
	Motor Output x Number	W	375 x 1	375 x 1
	Running Current	A	1.36	2.15
	Full Load Amperes	A	2.15	2.15
	Air Flow Rate(H / M / L) (High Mode-factor set)	m³/min	23.7/13.2/13.2	35.7/23.7/23.7
		ft³/min	837/446/446	1261/837/837
	External Static Pressure	mmAq(Pa)	22	22
	Drive		Direct	Direct
	Motor type		BLDC	BLDC
Temperature Control			Microprocessor, Thermostat for cooling and heating	Microprocessor, Thermostat for cooling and heating
Sound Absorbing Thermal Insulation Material			Foamed polystyrene	Foamed polystyrene
Air Filter			Long Life Filter	Long Life Filter
Safety Device			Fuse	Fuse
Pipe Connections	Liquid Side	mm(inch)	Ø9.52(3/8)	Ø9.52(3/8)
	Gas Side	mm(inch)	Ø19.05(3/4)	Ø22.2(7/8)
	Drain Pipe(Internal Dia.)	mm(inch)	25	25
Net Weight		kg(lbs)	73(161)	73(161)
Sound Pressure Levels (H / M / L)		dB(A)	45 / 43 / 43	47 / 45 / 45
Sound Power Levels (H / M / L)		dB(A)	70 / 67 / 67	72 / 70 / 70
Power Supply		Ø, V, Hz	1, 220 - 240, 50	1, 220 - 240, 50
			1, 220, 60	1, 220, 60
Refrigerant Control			EEV	EEV
Transmission cable		mm²	1.0~1.5 x 2C	1.0~1.5 x 2C