

Model Name		Unit	APNW55GT3E4 / APNW55GT3M4
Power Supply	#1	V, Φ , Hz	230, 1, 60
	#2		230, 1, 50
Power Input	Max.	W	-
Running Current	Max.	A	-
Indoor Fan	Type	-	Sirocco
	Air Flow Rate(SH/H/M/L)	m ³ /min	37.0 / 33.0 / 28.0 / 24.0
Indoor Fan Motor	Type	-	BLDC
	Drive	-	-
	Output	W x No.	224 x 1
	FLA(Full Load Ampere)	A	0.95
Dehumidification Rate	-	ℓ/h	4.9
Heat Exchanger	(Rows x Columns x FPI) x No.	-	(3 x 38 x 19) x 1
	Face Area	m ²	0.39
Dimensions	Net(W x H x D)	mm	590 × 1,840 × 440
	Shipping(W x H x D)	mm	690 × 1,940 × 531
Weight	Net	kg	49.0
	Shipping	kg	57.0
Exterior	Color	-	Noble white
Protection Divice	-	-	Fuse
Refrigerant	Control Type	-	Electronic Expansion Valve
Drain Pipe	O.D / I.D	mm	Ø 21.0 / 17.0
Piping Connection	Liquid	mm(inch)	Ø 9.52 (3/8)
	Gas	mm(inch)	Ø 19.05 (3/4)
Sound Pressure Level	Cooling(SH/H/M/L)	dB(A)	55.0 / 52.0 / 49.0 / 47.0
	Heating(SH/H/M/L)	dB(A)	55.0 / 52.0 / 49.0 / 47.0
Sound Power Level	Cooling(SH/H/M/L)	dB(A)	-
	Heating(SH/H/M/L)	dB(A)	-
Connecting Cable	Power and Communication cable (H07RN-F)	mm ² × cores	0.75 x 4