32" CLASS (31.5" DIAGONAL) 26" CLASS (26.0" DIAGONAL) 22" CLASS (21.9" DIAGONAL)

Hospital Grade LCD Widescreen HDTV with HD-PPV Capability

DESIGNED SPECIFICALLY FOR THE HEALTHCARE INDUSTRY

UL HOSPITAL GRADE LISTED Built-in Pillow Speaker Port Built-in Card Slot (MPI™ Interface) Rear Speaker Disable Switch

32LG3DDH

26LG3DDH 22LG3DDH

IMPROVED! EXPANDED PILLOW SPEAKER COMPATIBILITY Supports multiple codes (Zenith, Philips, RCA)

> NEW! EXPRESS SCRIPT Easy to use, 7 Step Installer Menu Setup Wizard

NEW! MPEG-2/MPEG-4 H.264 DECODING

NEW! SPLASH IMAGE LOGO (ON STARTUP)

IMPROVED! CLEAR VOICE II

DYNAMIC POWER SAVINGS

USB CLONABLE

HD VOD PPV DECRYPTION AND INTERACTIVE SYSTEM CAPABILITY Integrated Pro:Idiom®

DIGITAL HD-PPV COMPATIBILITY

BUILT-IN ATSC/NTSC/CLEAR QAM TUNER

NATIVE DISPLAY RESOLUTION 1366 x 768 (32", 26" class) 1680 x 1050 (22" class)

DYNAMIC CONTRAST RATIO 12,000:1 (32", 26" class) 3,000:1 (22" class)

STANDARD VESA™ MOUNTING INTERFACE 200mm x 100mm (32", 26" class) 100mm x 100mm (22" class)

RESTRICTION OF HAZARDOUS SUBSTANCES (RoHS)

CALIFORNIA ENERGY COMMISSION (CEC) COMPLIANT

2 YEAR LIMITED WARRANTY (parts and labor)







"Your energy cost depends on your utility rates and use. The estimated cost is based on 11 cents per kWh and 5 hours of use per day. For more information, visit www.ftc.gov/energy."

¹FTC Television labeling rule (18 CFR Part 305, as added by 76 Fed. Reg. 1038 (Jan 6, 2011)).

ENERGY GUIDE

LG solutions.com



WHEN IT'S GREEN.

LG is committed to improving product development, manufacturing and usage to meet the demand for environmentally friendlier products. Our LG3DDH series televisions have technologies to reduce power consumption and in return increase cost savings per room.

EcoSmart

- Dynamic Power Savings Using built-in algorithms, the TV will automatically reduce the power consumption based on incoming video, while maximizing picture performance.
- Static Power Savings Picture brightness level can be set at the preferred power consumption level to reduce power and increase energy savings.
- CEC Compliant Meets the Appliance Efficiency Regulations of the California Energy Commission.
- RoHS Compliant Meets directive on restriction of hazardous substances.
- Power Management Automatic shutoff when TV has no activity after selected 1 -7 hours of operation.

ECIAL FEAT

32LG3DDH (silver) 26LG3DDH (silver)



22LG3DDH (silver)



Pro:Idiom

DIGITAL RIGHTS MANAGEMENT SYSTEM

The Pro:Idiom system's high-quality security unlocks access to premium content availability to help assure rapid, broad deployment of HDTV and other high value digital content. Pro:Idiom has been designed specifically for industries that use premium HDTV content from cable, satellite or video on demand (VOD) services and as such, could result in lower costs, and reduced maintenance. This system is one of the leading DRM systems embraced by content providers for both of these key programming sources. By using this embedded approach, security is provided and helps eliminate the possibility of customers tampering with or removing needed components.

To view and to ensure proper operation of Pro:Idiom channels, additional equipment and programming services may be required.

MPEG-4 TECHNOLOGY (Moving Picture Experts Group)

MPEG-4 decodes and delivers high-definition programming it receives via satellite. The advanced coding system is compatible with national and local HD channels, along with digital HD channels currently launched by DIRECTV. LG built this technology into its LG3DDH series TVs to deliver pure HD without the need for an external box*.

* Certain functions, such as Pay-Per-View, may require a set-top box.

EXPRESS SCRIPT INSTALLER MENU WIZARD

The Express Script Installer Menu Wizard enables users to customize essential items for viewing the TV the first time it is turned on. This 7 step process is a convenient and easy way to provide the preferred settings recommended by the facility. The Express Script Installer Menu Wizard can also be activated from the commercial installer menu.



POWER SAVING LEVELS

By selecting lower levels of backlight settings, a reduction in power consumption is achieved resulting in energy savings and lower costs.

32LG3DDH in Vivid Mode		
BACKLIGHT SETTING VALUE	BRIGHTNESS (cd /m²)	* POWER CONSUMPTION (Watts)
Level 100	290 cd/m ²	76Watts
90	90%**	91%**
80	83%	86%
70	74%	83%
60	67%	79%
50	61%	75%
40	53%	70%
30	51%	68%
20	46%	64%
10	34%	55%
1	26%	49%

* Power consumption was measured using IEC62087 dynamic broadcast - content video signal

** All percentages listed are percentages based off of level 100

BRIGHTNESS (cd /m²) BACKLIGHT Level 100 290 (cd /m²) 86%** 90 80 77%

26LG3DDH in Vivid Mode

20

EXPRESS

SCRIPT

* POWER CONSUMPTION 61 W 90%** 83% 70 69% 61% 71% 60 50 40 53% 49% 68% 66% 30 44% 63%

58%

55% 50%

40%

32%

23%

22LG3DDH in Vivid Mode

BACKLIGHT SETTING VALUE	BRIGHTNESS (cd /m²)	* POWER CONSUMPTION (Watts)
Level 100	214 cd/m ²	44 Watts
90	91%**	95%**
80	81%	90%
70	74%	86%
60	65%	81%
50	58%	77%
40	51%	70%
30	46%	73%
20	39%	64%
10	29%	59%
1	21%	53%



BRIGHTER

CLEARER






Э (O)

Six distinct processes contribute to picture improvement. LG's XD Engine takes the low resolution of analog signals to near HD levels by improving brightness, contrast, detail and enhancing color as well as reducing signal noise.

CLONING OPTIONS

The LG3DDH series has a convenient time and expense saver feature. A select number of commercial menu items are cloning capable. This allows the cloning of a master TV to an infinite number of the same model target TV. This can be easily accomplished in either of two ways, by using a USB memory device or by using an optional LG accessory TLL-1100A TVLink-Loader. This time saving technique will allow the installers to program the preferred commercial settings from a master TV to all the required target televisions in a hospital facility in a matter of just a few minutes per TV.

Clone using a USB Memory Device




The Installer sets up a master TV with the preferred menu settings. A USB memory device is plugged into the master TV. Menu items are selected to "Learn From TV" and stored on the USB memory device. The USB stick is then plugged into a target TV. Menu items are selected to "Teach To TV". The USB device is then unplugged and is ready to engage with the next target TV.



Clone using OPTIONAL TLL-1100A TVLink-Loader



The Installer sets up a master TV with the preferred menu settings. The TLL-1100A TVLink-Loader is charged up and the MPI cable is connected to both the TLL-1100A and the Master TV. By selecting buttons on this TVLink-Loader, menu items are selected to "Learn From TV" and stored on the TLL-1100A (about 90 seconds). The TLL-1100A is then plugged into a target TV. By selecting buttons on the TVLink-Loader, the TLL-1100A menu items are selected to "Teach To TV". The TVLink-Loader is then unplugged and is ready to engage with the next target TV.



32LG3DDH

26LG3DDH

22LG3DDH

32" CLASS (31.5" DIAGONAL)

26" CLASS (26.0" DIAGONAL)

22" CLASS (21.9" DIAGONAL)

22 CLA33 (21.9 DIA	JONAL
DISPLAY	
LCD Panel Type	22", 26", 32" class
Display Area	21.9", 26.0", 31.5" diagonal
Aspect Ratio	16:9
Native Resolution	1680 x 1050 (22"), 1366 x 768 (26", 32")
Pixels (H×V×3)	5,292,000 (22"), 3,147,264 (26", 32")
Dynamic Contrast Ratio	3,000:1(22"), 12,000:1(26", 32")
Contrast Ratio	1000:1(22"), 3,000:1(26", 32")
Viewing Angle (Horizontal/Vertical)	160°/160°(22″), 178°/178°(26″, 32″)
Color Depth	8bit (16.7M)
Lamp Life	50,000 hours (approx.)
Response Time	5ms (22"), 6ms (26", 32")
MAIN SYSTEM	
MPEG Decoder	MPEG2/MPEG4 /H.264 Decoding
Maximum Computer Resolution (RGB)	
VIDEO	1000 X / 00
ATSC/NTSC/QAM Clear Tuner	Yes (Built-in)
ATSC/W13C/QAM Cledi Toner ATSC with HD-PPV	Yes (Built-in)
All Format Convertor	Yes (1080p/1080i/720p/480p/480i >1050p) (22")
Air offici Converior	(1080p/1080i/720p/480p/480i > 768p) (22") (1080p/1080i/720p/480p/480i > 768p) (26", 32")
Comb Filter	Yes (3D Digital)
Digital Progressive Scan	Yes
Color Temperature	
Enhanced Video	Yes (Cool/Normal/Warm) Yes
Advanced Ghost Canceler	Yes
DLTI (Digital Luminance Transient Limiter	
DCTI (Digital Color Transient Improver)	
Black/Blue Stretcher	Yes
3:2 Pull-Down (film mode)	Yes
Aspect Ratio	5 Modes (16:9/Just Scan/Set By Program/4:3/Zoom)
Picture Control	Backlight/Contrast/Brightness/Sharp/Color/Tint/
	Advanced
Noise Reduction	Yes
XD Engine	Yes
EZ Picture	6 Modes
	(Vivid/Standard/Natural/Cinema/Sport/Game)
AUDIO	0
# of Speaker	2
Dolby Digital® Decoder	Yes
Mono/Stereo/SAP	Yes Infinite Sound
Surround System Clear Voice II	
Total Audio Watts (RMS)	Yes
Ioral Audio Watts (RMS)	2 x 3W (6W) (22"), 2 x 7 W (14W) (26"),
	2 x 10W (20W) (32")
Bass/Treble/Balance	Yes
EZ SoundRite (Auto Volume Leveler)	
EZ Sound	5 Modes (Standard, Music, Cinema, Sports, Game)
Internal Speaker on/off	Yes
SPECIAL FEATURES	
Power saving function	Backlight dimming control
USB Cloning	Yes
Integrated Pro:Idiom	Yes
OSD Type (Menu System)	EZ Menu
Express Script	Yes
Trilingual Menus	Yes (English, French, Spanish)
Commercial Installation Menu	Yes (English only)
TV Link Protocol	TV Link-Commercial (built in)
Discrete IR Codes	Yes
Real Cinema	Yes
Auto Off	Yes

LGsolutions.com

LG Electronics U.S.A., Inc. Commercial Displays 2000 Millbrook Drive Lincolnshire, IL 60069

Customer Service: 888.865.3026 www.LGsolutions.com/support

Contact your LG Regional Sales Representative Healthcare/Long Term Care (In-Room Solutions): 800.228.1236 Channel (Reseller): 800.897.8871 Vertical Markets /SMB (Digital Signage Solutions): 800.897.8788 E-mail: info@LGsolutions.com

Last Source Power-on Recall	Yes
Auto/Manual Clock	Yes
On/Off Timer	Yes
Sleep Timer	Yes
Auto/Manual Programming	Yes
Channel Labeling	Yes
Favorite Channel	No
Closed Caption	Analog/Digital
Mute	Yes
Flashback (Quick View)	Yes
Parental Control/V-Chip	Yes
Function Menu	Yes
Remote	Not Included
JACKS	- tor incloded
RF in	1 (NTSC+ATSC tuner)
A/V In	1 (Rear) (22"), 2 (Rear/Side) (26", 32")
S-Video In	No
Component & R/L Audio In	1 (Rear) (except 22")
RGB In (DB15-RGB)	1 (Rear) (except 22")
Audio in (Phone Jack)	1 (Rear: PC) (except 22")
HDMI	1 (Rear)
Speaker Out (Bathroom)	Yes (8 ohm mono 1W Phone Jack) (except 22")
Earphone Jack	Yes (Side) (26", 32"), (Front) (22")
Pillow Speaker	1(6-pin)
	Yes (Zenith/RCA/Philips)
Pillow Speaker Codes	
RS-232C (Service Only) IR In/out	1 (Rear)
USB	
	1 (Cloning and Service)
MPI Slot	1 Slot (Standard Type)
OPTIONAL REMOTES	
Installer Remote	124-213-07 (Bed 1/Bed 2, TV menu & navigation buttons)
Patient Remote	124-213-08 (Bed 1/Bed 2)
"Clone" Programmers	TLL-1100A
REQUIRED CERTIFICATIONS	X/
UL, C-UL, NOM	Yes
UL Hospital Grade	Yes
RoHS Compliant	Yes
CEC Compliant	Yes
CABINET	C:1
Color	
Power/Standby Indicator	Illuminates red in standby mode/green in on mode
Unit Dimensions (WxHxD)	31.6" x 21.4" x 4.3" (32")
	26.1" x 17.6" x 4.1" (26")
	20.8" x 15.3" x 3.3" (22")
Unit Weight	26.2 lbs (32")
	20.95 lbs (26")
	13.54 lbs (22")
Shipping Dimensions (WxHxD)	38.7" x 26.0" x 7.4" (32")
	32.4" x 21.5" x 8.1" (26")
	27.28" x 19.0" x 6.3" (22")
als show t	
Shipping Weight	36.8 lbs (32")
Shipping Weight	36.8 lbs (32") 26.0 lbs (26")
Shipping Weight	
	26.0 lbs (26")
Shipping Weight Invisible Speakers Kensington Security Slot	26.0 lbs (26") 18.5 lbs (22")
Invisible Speakers Kensington Security Slot	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin)
Invisible Speakers Kensington Security Slot	26.0 lbs (26") 18.5 lbs (22") Yes (Built-in) Yes
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface	26.0 lbs (26") 18.5 lbs (22") Yes (Buil-in) Yes 200mm x 100mm, M4 screws, (26", 32")
Invisible Speakers Kensington Security Slot VESA TM Standard Mount Interface UL Hospital Grade Power Cord	26.0 lbs (26") 18.5 lbs (22") Yes (Buil-in) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22")
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface UL Hospital Grade Power Cord Stand	26.0 lbs (26") 18.5 lbs (22") Yes (Buili-in) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes
Invisible Speakers Kensington Security Slot VESA TM Standard Mount Interface UL Hospital Grade Power Cord Stand POWER	26.0 lbs (26") 18.5 lbs (22") Yes (Buili-in) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes
Invisible Speakers Kensington Security Slot VESA TM Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings	26.0 lbs (26") 18.5 lbs (22") Yes (Buili-in) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes 110V 50/60Hz
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source Power Consumption (max.) with	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source Power Consumption (max.) with Power Saving Modes Disabled	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes 110V 50/60Hz 50W (22"), 80W (26"), 100W (32")
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source Power Consumption (max.) with Power Saving Modes Disabled Power Standy-by Mode (max.)	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes 110V 50/60Hz 50W (22"), 80W (26"), 100W (32") 1W
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source Power Consumption (max.) with Power Saving Modes Disabled Power Standy-by Mode (max.) SERVICE/LIMITED WARRANTY	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes 110V 50/60Hz 50W (22"), 80W (26"), 100W (32")
Invisible Speakers Kensington Security Slot VESA TM Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source Power Source Power Saving Modes Disabled Power Standy-by Mode (max.) SERVICE/LIMITED WARRANTY UPC CODE	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes 110V 50/60Hz 50W (22"), 80W (26"), 100W (32") 1W 2 Years (Parts/Labor)
Invisible Speakers Kensington Security Slot VESA™ Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source Power Consumption (max.) with Power Standy-by Mode (max.) SERVICE/LIMITED WARRANTY UPC CODE 32LG3DDH	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes 110V 50/60Hz 50W (22"), 80W (26"), 100W (32") 1W 2 Years (Parts/Labor) 7 19192 90158 2
Invisible Speakers Kensington Security Slot VESA TM Standard Mount Interface UL Hospital Grade Power Cord Stand POWER Dynamic/Static Power Savings Power Source Power Source Power Saving Modes Disabled Power Standy-by Mode (max.) SERVICE/LIMITED WARRANTY UPC CODE	26.0 lbs (26") 18.5 lbs (22") Yes (Builtin) Yes 200mm x 100mm, M4 screws, (26", 32") 100mm x 100mm, M4 screws, (22") Yes Not included Yes 110V 50/60Hz 50W (22"), 80W (26"), 100W (32") 1W 2 Years (Parts/Labor)

All screen images are simulated. Dimensions and weights are approximate. Design, features and specifications subject to change without notice.

© Copyright 2011 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp. XD Engine is a registered trademark of LG Electronics USA, Inc. Pro:Idiom is a registered trademark and MPI is a trademark of Zenith Electronics Corp. Dolby and the double-D symbol are registered trademarks of Dolby Laboratories. SRS and the SRS symbol are registered trademarks of SRS Labs, Inc. in the U.S. and selected foreign countries. TruSurround XT is a trademark of SRS Labs, Inc. VESA is a trademark of Video Electronics Standards Association. All other product and brand names are trademarks or registered trademarks of their respective companies.



SPEC_LG3DDH_101124_PR