



Slim Direct LED **Commercial Widescreen** with Commercial Grade Stand

▶ 55LY340H

55" class (54.64" measured diagonally)

▶ 47LY340H

47" class (46.96" measured diagonally)

▶ 42LY340H

42" class (41.92" measured diagonally)

▶ 39LY340H

39" class (39.0" measured diagonally)

▶ 32LY340H

32" class (31.51" measured diagonally)



Optimized Features for Commercial Use

FOR EFFICIENT MANAGEMENT



PUBLIC DISPLAY MODE
From channel selection to energy-saving features, Public
Display Mode allows you to control the TV settings in your
Hotel, which prevents misuse by customers, set volume limits, or restore factory defaults on any TV. You are in





USB CLONING

The USB Cloning feature allows you to simply copy the TV settings onto all TVs using a USB stick, a process that is fully automated to save time without having to set each TV one by one.





WELCOME SCREEN

Welcome guests with a warm greeting message that includes your hotel name and logo





MHL (MOBILE HIGH-DEFINITION LINK)

MHL connects smart phones to the TV instantly, mirroring content in HD quality, just like connecting a PC through an HD cable. Moreover, it allows you to control the phone's content on the TV with a remote control.





MULTI IR
Multi IR function eliminates the remote control signal interference between TVs in multiple dwelling rooms. This system will work using the same LG TV model.

(Optional 124-213-10 required)





RS232C CONTROL
Via the TV's RS-232C port, you can remotely control multiple TVs' power and volume settings simultaneously.



FOR CONVENIENCE & ENTERTAINMENT



EXTERNAL SPEAKER OUT

Enhance the entertainment experience by adding an additional speaker, allowing TV audio to be heard from other locations such as the bathroom.





IR Out enables set-top boxes to receive IR signals via LG TV Signage. This added convenience requires only simple connections and allows easy management using a single remote control.





USB 2.0 You can play images and videos from external storage devices.















Slim Direct LED **Commercial Widescreen** with Commercial Grade Stand

▶ 55LY340H

55" class (54.64" measured diagonally)



47" class (46.96" measured diagonally)



42" class (41.92" measured diagonally)


▶ 39LY340H

39" class (39.0" measured diagonally)

▶ 32LY340H

32" class (31.51" measured diagonally)

SDECIAL Model



PANEL	Model	55LY340H	4/LY340H	42LY340H	39LY340H	32LY340H		
	Panel Technology	Direct LED						
	Panel Size (Measured Diagonally)	55" Class (54.64")	47" Class (46.96")	42" Class (41.92")	39" Class (39.0")	32" Class (31.51")		
	Native Resolution	1920 x 1080 (FHD) 1366 x 768 (F						
	Brightness cd/m ²	300 cd/m ²						
	Static (Panel) Contrast Ratio	1,200:1			1,100:1	1,200:1		
	Viewing Angle (HxV)	178°/178°						
	Frame Rate	60Hz						
BROADCASTING	Analog	Yes (NTSC)						
SYSTEM	Digital	Yes (ATSC / Clear QAM)						
AUDIO	Audio Output	10W + 10W						
	Speaker System	2.0 ch						
SPECIAL FEATURES	MHL	Yes						
	Self Diagnostics	Yes						
	HDMI-CEC	Yes						
	HTNG-CEC	Yes						
	Welcome Screen	The state of the s						
	Lock Mode	Yes						
	Multi IR Code	Yes						
	Public Display Mode	Yes						
	USB Cloning	Yes						
	IR Out	Yes						

EMERGY GUIDE *	4 " F
-------------------	-------------

The estimated annual energy cost determined in accordance with 16 CFR Part 305.5 for models 551Y340H, 47LY340H, 42LY340H, 39LY340H and 32LY340H are \$10, \$8, \$8, \$6 and \$5 respectively.

Your energy cost depends on your utility rates and use. The estimated cost is based on 11 cents per kWh and 5 hours of use per day. for more information, visit www.ltc.gov/energy."
FIC Television labeling rule (18 CFR Pari 305, as added by 76 Fed. Reg. 1038 (Jan 6, 2011)).

SPECIAL FEATURES (Cont.)	Wodet	33LT 34UFI	4/LT340H	42L1 34UH	39LT 34UFI	32LT 340H		
	USB Auto Play Back	Yes						
	External Speaker Out	Yes (3.5mm Phone Jack)						
	RJP Compatibility	Yes (HDMI-CEC)						
	Kensington Lock	Yes						
	Credenza/Security Screw Hole	Yes						
	Lock Down Plate	Yes						
INTERFACE (Side)	HDMI In	1 Side						
	USB (2.0)	1 Side						
INTERFACE	RF In	1 Rear						
(Rear)	AV In (Composite)	1 Rear (Sharing with Component In)						
	Component in (Y,Pb,Pr) + Audio (L/R)	1 Rear						
	Digital Audio Out (Optical)	1 Rear						
	RGB In (D-sub 15pin) - PC	1 Rear						
	PC Audio Input	1 Rear (Sharing with Component In)						
	RS-232C (DSub 9pin)	1 (Control & Service)						
	HDMI In	1 Rear						
	External Speaker Out	1 Rear (3.5mm Phone Jack)						
CABINET	Bezel Width (on Bezel) (mm)	11.0mm/8.5mm			10.5mm/ 9mm	11.6mm/ 10.5mm		
	Bezel Width (Depth) (mm)	56.8mm	55.8mm	55.5mm				
	With Stand	48.9" x 30.4" x 12.8"	42.2"×26.8"×12.8"	37.8" × 24.3" × 12.8"	34.8" x 22.4" x 11.1"	28.8" x 19.0" x 11.1"		
	Weight	47.2 lbs	34.6 lbs	27.8 lbs	24.0 lbs	19.6 lbs		
	Without Stand	48.9"×28.3"×2.2"	42.2"×24.5"×2.2"	37.8" × 22.1" × 2.2"	34.8"×20.4"×2.2"	28.8" x 17.0" x 2.2"		
	Weight	39.7 lbs	27.1 lbs	20.3 lbs	17.6 lbs	13.2 lbs		
	Carton	52.4" x 32.7" x 7.5"	45.3" x 28.7" x 6.4"	41.7"×28.7"×6.4"	38.8" x 24.0" x 6.0"	32.1"×20.0"×75"		
	Weight	56.9 lbs	42.8 lbs	30.4 lbs	28.4 lbs	23.6 lbs		
	Swivel	Yes (± 20), with Lock Down plate (±20/45/90°)						
	C 1			•				
	Color			Metallic Titar				
	Color VESA™ Standard Mount Interface		400mm x 400m	Metallic Titar		x 200mm		
REQUIRED	VESA™ Standard		400mm x 400m	Metallic Titar	200mm	x 200mm		
REQUIRED LISTINGS	VESA TM Standard Mount Interface		400mm x 400m	Metallic Titar	200mm	x 200mm		
LISTINGS	VESA TM Standard Mount Interface Safety		400mm x 400m	Metallic Titar m cUL, UL, FCC, N	200mm	x 200mm		
REQUIRED LISTINGS	VESA TM Standard Mount Interface Safety RoHS		400mm x 400m	Metallic Titar m cUL, UL, FCC, No Yes Yes	200mm OM	x 200mm 7 19192 91754 5		
LISTINGS	VESA TM Standard Mount Interface Safety RoHS		400mm x 400m 4 7 19192 91756 9	Metallic Titar m cUL, UL, FCC, No Yes Yes	200mm OM 7 19192 91764 4			
UPC UPC	VESA™ Standard Mount Interface Safety RoHS Energy Star 6.1		400mm x 400m 4 7 19192 91756 9	Metallic Titar m EUL, UL, FCC, No Yes Yes 7 19192 91755 2	200mm OM 7 19192 91764 4			
UPC UPC	VESA TM Standard Mount Interface Safety RoHS Energy Star 6.1 Power Source Power Cord		400mm x 400m 4 7 19192 91756 9	Metallic Titar m cUL, UL, FCC, No Yes Yes 7 19192 91755 2 0 ~ 240V, 50/	200mm OM 7 19192 91764 4			
UPC UPC	VESA™ Standard Mount Interface Safety RoHS Energy Star 6.1 Power Source Power Cord Length	7 19192 91757 6	400mm x 400m (7 19192917569	Metallic Titar m SUL, UL, FCC, No Yes Yes 7 19192 91755 2 0 ~ 240V, 50/0	200mm OM 7 19192 91764 4 50Hz	7 19192 91754 5		

55LY340H 47LY340H 42LY340H 39LY340H 32LY340H





Contact your LG Regional Sales Representative: Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com

SPEC_LY340Hseries_051423_PR





HDMI









2 Year Limited Warranty (Parts/Labor)









 $\textbf{All screen images are simulated.} \ Dimensions \ and \ weights \ are \ approximate. \ Design, features \ and \ specifications \ subject to \ change \ without \ notice.$

© Copyright 2014 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp. XD Engine is a registered trademark of LG Electronics, Inc. HealthView and EcoSmart are trademarks of LG Corp. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency Dolby and the double-D symbol are registered trademarks of Dolby Laboratorics STS and the SRS symbol, TruSurround XT and WOW are trademarks or registered trademarks of SRS Labs, Inc. VESA is a trademark of Video Electronics Standards Association. All other product and brand names are trademarks or registered trademarks of their respective companies.



