



LG NeON[®] 72cell

LG360N2W-B3

72 cell

Introducing LG NeON[®] 72 cell module series, which uses highly efficient n-type materials, an elaborate process control adopting a semiconductor processing solution and a double-sided structure. Our R&D concentrates on developing a product that is not only efficient, but strives to increase practical value for customers.



Enhanced Performance Warranty

LG NeON[®] 72 cell has an enhanced performance warranty. The annual degradation has fallen from -0.7%/yr to -0.6%/yr. Even after 25 years, the cell guarantees 2.4%p more output than the previous LG NeON[®] modules.



N-Type Material

LG NeON[®] 72 cell uses n-type cells, boasting higher mobility of electric charge, resulting in higher generation efficiency.



Better Performance on a Sunny Day

LG NeON[®] 72 cell now performs better on a sunny days thanks to its improved temperature coefficient.




High Power Output

Compared with previous models, the LG NeON[®] 72 cell has been designed to significantly enhance its output efficiency making it efficient even in limited space.



Double-Sided Cell Structure

The rear of the cell used in LG NeON[®] 72 cell is designed to contribute to generation; the light beam reflected from the rear of the module is reabsorbed to generate a great amount of additional power.



Near Zero LID (Light Induced Degradation)

The n-type cells used in LG NeON[®] 72 cell have almost no boron, which may cause the initial efficiency to drop, leading to less LID.



About LG Electronics

LG Electronics is a global player who has been committed to expanding its operations with the solar market. The company first embarked on a solar energy source research programs in 1985, supported by LG Group's vast experience in the semi-conductor, LCD, chemistry, and materials industries. In 2010, LG Solar successfully released its first Mono X[®] series to the market, which is now available in 32 countries. The LG NeON[®] (previous Mono X[®] NeON) and the LG NeON[®] 2 won the "Intersolar Award" in 2013 and 2015, which demonstrates LG Solar's lead, innovation and commitment to the industry.

Mechanical Properties

Cells	6 x 12
Cell Vendor	LG
Cell Type	Monocrystalline / N-type
Cell Dimensions	156.75 x 156.75 mm / 6 inches
# of Busbar	3
Dimensions (L x W x H)	1960 x 1000 x 46 mm 77.17 x 39.37 x 1.81 inch
Front Load	60 psf
Rear Load	60 psf
Weight	20.3 ± 0.5 kg / 44.75 ± 1.1 lbs
Connector Type	MC4, IP67
Junction Box	IP67 with 3 bypass diodes
Cable	PV wire 12 AWG (4.0mm ²) conductor
Length of Cables	2 x 1200 mm / 2 x 47.24 inch
Glass	High Transmission Tempered Glass
Frame	Anodized Aluminium

Certifications and Warranty



Certifications	IEC 62716 (Ammonia Test) IEC 61701 (Salt Mist Corrosion Test) ISO 9001 UL 1703
Module Fire Performance (USA)	Type 2 (UL 1703)
Fire Rating (for CANADA)	Class C (ULC/ORD C1703)
Product Warranty	12 years 
Output Warranty of Pmax	Linear warranty* 

* 1) 1st year: 98%, 2) After 2nd year: 0.6%p annual degradation, 3) 83.6% for 25 years

Temperature Characteristics

NOCT	45 ± 2 °C
Pmax	-0.41 %/°C
Voc	-0.30 %/°C
Isc	0.04 %/°C

Characteristic Curves



Electrical Properties (STC *)

Module Type	360 W
MPP Voltage (Vmpp)	38.4
MPP Current (Impp)	9.39
Open Circuit Voltage (Voc)	48.3
Short Circuit Current (Isc)	9.84
Module Efficiency (%)	18.4
Operating Temperature (°C)	-40 ~ +90
Maximum System Voltage (V)	1000
Maximum Series Fuse Rating (A)	20
Power Tolerance (%)	0 ~ +3

* STC (Standard Test Condition): Irradiance 1000 W/m², Module Temperature 25 °C, AM 1.5

* The nameplate power output is measured and determined by LG Electronics at its sole and absolute discretion.



* The typical change in module efficiency at 200 W/m² in relation to 1000 W/m² is -2.0%.

Electrical Properties (NOCT*)

Module Type	360 W
Maximum Power (Pmax)	263
MPP Voltage (Vmpp)	35.2
MPP Current (Impp)	7.49
Open Circuit Voltage (Voc)	44.8
Short Circuit Current (Isc)	7.93

* NOCT (Nominal Operating Cell Temperature): Irradiance 800 W/m², ambient temperature 20 °C, wind speed 1 m/s

Dimensions (mm/in)



* The distance between the center of the mounting/grounding holes.

