


# LG NeON<sup>®</sup> 2

LG395N2W-V5 | LG400N2W-V5



72

## 395W | 400W

The LG NeON<sup>®</sup> 2 is LG's best selling solar module, and is one of the most powerful and versatile modules on the market today. Featuring LG's Cello Technology, the LG NeON<sup>®</sup> 2 increases power output. New updates include an extended performance warranty from 86% to 89.6% to give customers higher performance and reliability.



## Features



### Enhanced Performance Warranty

LG NeON<sup>®</sup> 2 has an enhanced performance warranty. After 25 years, LG NeON<sup>®</sup> 2 is guaranteed at least 89.6% of initial performance.



### Enhanced Product Warranty

LG has extended the warranty of the NeON<sup>®</sup> 2 to 25 years including labor, which is top level in the industry.



### Better Performance on a Sunny Day

LG NeON<sup>®</sup> 2 now performs better on sunny days, thanks to its improved temperature coefficient.



### BOS (Balance Of System) Saving

LG NeON<sup>®</sup> 2 can reduce the total number of strings due to its high module efficiency resulting in a more cost effective and efficient solar power system.

**When you go solar, ask for the brand you can trust: LG Solar**

## About LG Electronics

LG Electronics is a global leader in electronic products in the clean energy markets by offering solar PV panels and energy storage systems. The company first embarked on a solar energy source research program in 1985, supported by LG Group's vast experience in the semi-conductor, LCD, chemistry and materials industries. In 2010, LG Solar successfully released its first MonoX<sup>®</sup> series to the market, which is now available in 32 countries. The NeON<sup>®</sup> (previous MonoX<sup>®</sup> NeON), NeON<sup>®</sup>2, NeON<sup>®</sup>2 BiFacial won the "Intersolar AWARD" in 2013, 2015 and 2016, which demonstrates LG's leadership and innovation in the solar industry.

# LG Solar

### General Data

Cell Properties (Material / Type)	Monocrystalline / N-type
Cell Maker	LG
Cell Configuration	72 Cells (6 x 12)
Number of Busbars	12EA
Module Dimensions (L x W x H)	2,024mm x 1,024mm x 40 mm
Weight	20.3 kg
Glass (Material)	Tempered Glass with AR Coating
Backsheet (Color)	White
Frame (Material)	Anodized Aluminium
Junction Box (Protection Degree)	IP 68
Cables (Length)	1,200mm x 2EA
Connector (Type / Maker)	MC 4 / MC

### Certifications and Warranty

Certifications	IEC 61215-1/-1-1/2:2016, IEC 61730-1/2:2016, UL 1703 ISO 9001, ISO 14001, ISO 50001 OHSAS 18001
Salt Mist Corrosion Test	IEC 61701:2012 Severity 6
Ammonia Corrosion Test	IEC 62716:2013
Module Fire Performance	Type 1 (UL 1703)
Fire Rating	Class C (UL 790, UL/ORD C 1703)
Solar Module Product Warranty	25 Years
Solar Module Output Warranty	Linear Warranty*

\* 1) 1st year: 98% 2) After 1st year: 0.35% annual degradation, 3) 89.6% for 25 years

### Temperature Characteristics


NMOT*	[°C]	42 ± 3
Pmax	[%/°C]	-0.36
Voc	[%/°C]	-0.26
Isc	[%/°C]	0.02

\* NMOT (Nominal Module Operating Temperature). Irradiance 800 W/m<sup>2</sup>, Ambient temperature 20 °C, Wind speed 1 m/s, Spectrum AM 1.5

### Electrical Properties (NMOT)

Model		LG395N2W-V5	LG400N2W-V5
Maximum Power (Pmax)	[W]	296	300
MPP Voltage (Vmpp)	[V]	37.7	38.0
MPP Current (Impp)	[A]	7.86	7.88
Open Circuit Voltage (Voc)	[V]	46.4	46.5
Short Circuit Current (Isc)	[A]	8.37	8.40

### I-V Curves



### Electrical Properties (STC\*)

Model		LG395N2W-V5	LG400N2W-V5
Maximum Power (Pmax)	[W]	395	400
MPP Voltage (Vmpp)	[V]	40.2	40.6
MPP Current (Impp)	[A]	9.83	9.86
Open Circuit Voltage (Voc, ± 5%)	[V]	49.2	49.3
Short Circuit Current (Isc, ± 5%)	[A]	10.43	10.47
Module Efficiency	[%]	19.1	19.3
Power Tolerance	[%]	0 ~ +3	

\* STC (Standard Test Condition): Irradiance 1000 W/m<sup>2</sup>, cell temperature 25 °C, AM 1.5

### Operating Conditions

Operating Temperature	[°C]	-40 ~ +90
Maximum System Voltage	[V]	1,500(UL), 1000(IEC)
Maximum Series Fuse Rating	[A]	20
Mechanical Test Load (Front)	[Pa/psf]	5,400 / 113
Mechanical Test Load (Rear)	[Pa/psf]	3,000 / 63

\* Test Load = Design load x Safety Factor (1.5)

### Packaging Configuration

Number of Modules per Pallet	[EA]	25
Number of Modules per 40ft HQ Container	[EA]	550
Packaging Box Dimensions (L x W x H)	[mm]	2,080 x 1,120 x 1,226
Packaging Box Gross Weight	[kg]	551

### Dimensions (mm / inch)

