
Vibrant Colors and Powerful Performance Bring Content to Life

UH5E Series (65" / 55" / 49")

With superb picture quality and cutting-edge processing power, the UH5E series delivers a value-added visual experience without the need for peripherals. It delivers vivid content with no reflections, even under bright lights, enhancing its ability to capture the attention of passersby. Moreover, the convenient yet advanced usability allows users to effortlessly control and manage the display.



Vibrant Colors and Powerful Performance Bring Content to Life

UH5E Series (65" / 55" / 49")

Superior Picture Quality

True Color, Immersive View

The UHD resolution delivers more detailed and vivid content without distortion, with four times higher definition than FHD. The UH5E series ensures stable UHD video playback by supporting HEVC (High Efficiency Video Coding).



Clear View with Non-glare Coating

Viewers can easily become frustrated by unnecessary reflections when watching a screen under brightly lit conditions. The UH5E series has resolved this problem by increasing the haze value up to 28%, enhancing content visibility and text readability.



Vibrant Colors and Powerful Performance Bring Content to Life

UH5E Series (65" / 55" / 49")

High Compatibility

Compatibility with AV Control System

The UH5E series has been certified Crestron Connected[®] for a higher level of compatibility with professional AV controls to achieve seamless integration and automated control*, boosting business management efficiency.



* Network-based control

Compatibility with Video Conference System

For the optimum visual meeting, the UH5E series has certified its compatibility with Cisco Spark Room Kits, a system that offers powerful and integrated control* for a smarter video conference, eliminating a waste of time to set up the picture quality or to change input on incoming calls.



* Using an HDMI cable connection

Vibrant Colors and Powerful Performance Bring Content to Life

UH5E Series (65" / 55" / 49")

Wireless Solution

Content Sharing

Content mirroring among devices is more convenient on a Wi-Fi network.

Real-time Promotion

With Beacon and BLE (Bluetooth Low Energy), shop managers can provide coupons and information in real-time.

Wireless Access Point

The UH5E series operates as a virtual router which can be an wireless access point for mobile devices.



Vibrant Colors and Powerful Performance Bring Content to Life

UH5E Series (65" / 55" / 49")

Easy Maintenance

Real-Time Monitoring & Control

Through the Control Manager, the embedded web monitoring solution, you can control and monitor the status of multiple displays in different locations in real-time. It is available on internet-connected devices, allowing you to flexibly and rapidly respond to emergency situations anywhere.



Real-time Care Service

The maintenance gets easier and faster with an optional service Signage 365 Care*, a cloud service solution provided by LG service. It remotely manages status of displays in client workplaces for fault diagnosis and remote-control services, ensuring the stable operation of a client's business.



* The availability of "Signage 365 Care" service can differ by region, so please contact the LG sales representative in your region for further details.

Vibrant Colors and Powerful Performance Bring Content to Life

UH5E Series (65" / 55" / 49")

Powerful webOS Smart Signage Platform


Easy Content Management

The embedded CMS (Content Management System) allows you to create and edit content using internal or external sources as well as set playlists to play at the desired schedule without the need for a separate PC. Thanks to the intuitive GUI and a menu structure based on usage scenarios, content management has been made much easier.



Simple Group Management

The embedded Group Manager makes a master display work as a server and manage other displays* connected on the same network. This way you can group and control multiple displays in your place of business and distribute playlists to them all at once, using input devices such as a remote control.



* One master display can create a max. of 25 groups, and each group can consist of a max. of 12 slave displays.


Vibrant Colors and Powerful Performance Bring Content to Life

UH5E Series (65" / 55" / 49")

Powerful webOS Smart Signage Platform


Various Sensor Applications

LG webOS smart signage platform easily supports connections with external sensors such as GPIO, NFC/RFID, temperature sensors, etc. via USB plug-in. The overall cost of ownership is more affordable because there is no need to purchase additional software or media players for creating value-added solutions.





Multi Screen Mode

PBP (Picture-By-Picture) features multi screen in a single display with upto 4 input sources while PIP (Picture-In-Picture) supports playing both main screen and sub screen at the same time with various layouts. This gives great flexibility to allocate space for each content source.





Dimensions



65"



55"




49"



Connectivity

65" / 55" / 49"



- | | | |
|---------------|---------------------|---------------|
| 1 SPEAKER OUT | 6 IR & LIGHT SENSOR | 11 USB 1 |
| 2 LAN | 7 DP IN | 12 USB 2 |
| 3 HDMI 1 | 8 DP OUT | 13 AUDIO OUT |
| 4 HDMI 2 | 9 HDMI 3 | 14 RS232C IN |
| 5 AUDIO IN | 10 DVI-D IN | 15 RS232C OUT |

Specifications

	65UH5E	55UH5E	49UH5E		
PANEL	Screen Size	65	55	49	
	Panel Technology	IPS	IPS	IPS	
	Back Light Type	Edge	Edge	Edge	
	Aspect Ratio	16:9	16:9	16:9	
	Native Resolution	3840 x 2160 (UHD)	3840 x 2160 (UHD)	3840 x 2160 (UHD)	
	Refresh Rate	60Hz	60Hz	60Hz	
	Brightness (Typical)	500 nits	500 nits	500 nits	
	Contrast Ratio	1,100:1	1,100:1	1,100:1	
	Dynamic CR	1,000,000:1	1,000,000:1	1,000,000:1	
	Color gamut	68%	68%	68%	
	Viewing Angle(H x V)	178° x 178°	178° x 178°	178° x 178°	
	Color Depth	1.07 Billion	1.07 Billion	1.07 Billion	
	Response Time (G to G)	8 ms	8 ms	8 ms	
	Surface Treatment (Haze)	Haze 28%	Haze 28%	Haze 28%	
	Life time (Typ.)	50,000 Hrs	50,000 Hrs	50,000 Hrs	
	Operation Hours	24 Hrs	24 Hrs	24 Hrs	
	Orientation	Portrait & Landscape	Portrait & Landscape	Portrait & Landscape	
Overlay Touch Compatibility	No	No	No		
Input	Digital	HDMI	Yes (3), HDCP2.2	Yes (3), HDCP2.2	Yes (3), HDCP2.2
		DP	Yes (1), HDCP2.2	Yes (1), HDCP2.2	Yes (1), HDCP2.2
		DVI-D	Yes	Yes	Yes
	Analog	RGB	No	No	No
		Audio In	Yes	Yes	Yes
	External Control	RS232C IN	Yes	Yes	Yes
		RJ45(LAN)	Yes/bv	Yes	Yes
		IR IN	Yes	Yes	Yes
		USB	Yes (2), USB2.0	Yes (2), USB2.0	Yes (2), USB2.0
	Output	HDMI Out	No	No	No
DP Out		Yes	Yes	Yes	
Audio Out		Yes (1, Off/Fixed/Variable)	Yes (1, Off/Fixed/Variable)	Yes (1, Off/Fixed/Variable)	
External Speaker Out		Yes	Yes	Yes	
External Control		RS232C OUT	Yes (3.5mm)	Yes (3.5mm)	Yes (3.5mm)
		RJ45(LAN)	No	No	No
MECHANICAL SPECIFICATION	Bezel Color	Black	Black	Black	
	Bezel Width	12.1mm(T), 12.6mm(R/L), 15.7mm(B)	12.1mm(T), 12.6mm(R/L), 15.7mm(B)	11.9mm(T), 12.4mm(R/L), 15.5mm(B)	
	Monitor Dimensions (W x H x D)	57.4" x 33.4" x 1.6" / 1458.6mm x 848.9mm x 40.1mm	48.8" x 28.6" x 1.5" / 1239.8mm x 725.2mm x 38.6mm	43.4" x 25.5" x 1.4" / 1103.2mm x 648.0mm x 38.6mm	
	Weight	57.3 lbs / 26.0Kg	36.6 lbs / 16.6Kg	29.3 lbs / 13.3Kg	
	Weight(Head+Stand)	60.4 lbs / 27.4Kg	39.9" / 18.1Kg	32.6 lbs / 14.8Kg	
	Monitor with Optional Stand & Speaker Dimensions (W x H x D)	57.4" x 36.1" x 12.4" / 1458.6mm x 915.8mm x 313.9mm	48.8" x 31.1" x 11.7" / 1239.8mm x 788.8mm x 298.3mm	43.4" x 28.1" x 11.7" / 1103.2mm x 714.1mm x 298.3mm	
	Weight (Head+Stand+Speaker)	61.9 lbs / 28.1 kg	41.4 lbs / 18.8 kg	34.2 lbs / 15.5 kg	
	Carton Dimensions (W x H x D)	1561mm x 971mm x 190mm	1330mm x 807mm x 170mm	1197mm x 760mm x 166mm	
	Packed Weight	71.7 lbs / 32.5 kg	46.5 lbs / 21.1 kg	39 lbs / 17.7 kg	
	Handle	No	No	No	
	VESA/ATM Standard Mount Interface	300 x 300	300 x 300	300 x 300	
	HARDWARE	Internal Memory	8GB (System 4GB + Available 3.6GB)	8GB (System 4GB + Available 3.6GB)	8GB (System 4GB + Available 3.6GB)
		Wi-Fi (Built-in)	Yes	Yes	Yes
Sensor		Temperature Sensor	Yes	Yes	Yes
		Auto Brightness Sensor	Yes	Yes	Yes
		Current Sensor	Yes	Yes	Yes
Local Key Operation		Yes	Yes	Yes	

1) Network-based control 2) Compatibility may differ by equipment

	65UH5E	55UH5E	49UH5E		
SOFTWARE	webOS ver.	webOS 4.0	webOS 4.0	webOS 4.0	
	Embedded CMS	USB Auto Playback	Yes	Yes	Yes
		Local Contents Scheduling	Yes	Yes	Yes
		Group Manager	Yes	Yes	Yes
	Fail over	Yes	Yes	Yes	
	Image Customization	Booting Logo	Yes	Yes	Yes
		No Signal	Yes	Yes	Yes
	Content Sync.	RS-232C	Yes	Yes	Yes
		Local Network	Yes	Yes	Yes
	Multi-screen	PIP	Yes	Yes	Yes
		PBP	Yes (4)	Yes (4)	Yes (4)
	Screen Share		Yes	Yes	
	Video Tag	Yes (2)	Yes (2)	Yes (2)	
	Play via URL	Yes	Yes	Yes	
	OSD Rotation	Yes	Yes	Yes	
	Lock mode	Yes	Yes	Yes	
	Content Rotation	Yes	Yes	Yes	
	Gapless Playback	Yes	Yes	Yes	
	Tile Mode Setting	Yes (Max. 15x15)	Yes (Max. 15x15)	Yes (Max. 15x15)	
	Setting Data Cloning	Yes (RS-232C, Network, USB)	Yes (RS-232C, Network, USB)	Yes (RS-232C, Network, USB)	
	Firmware Update by Network	Yes	Yes	Yes	
	SNMP	Yes (Ver. 1.4)	Yes (Ver. 1.4)	Yes (Ver. 1.4)	
	ISM Mode (Image Sticking Minimization)	Yes	Yes	Yes	
	Auto Set ID	Yes	Yes	Yes	
	Status Mailing	Yes	Yes	Yes	
	Control Manager	Yes	Yes	Yes	
	Crestron Connected	Yes	Yes	Yes	
	Power Mgmt.	DPM	Yes	Yes	Yes
		On/Off Schedule	Yes	Yes	Yes
		Holiday Schedule	Yes	Yes	Yes
Power on Status		Standby, PWR, LST	Standby, PWR, LST	Standby, PWR, LST	
Energy Saving		Yes	Yes	Yes	
Smart Energy Saving		Yes	Yes	Yes	
PM mode		Yes	Yes	Yes	
Wake on LAN		Yes	Yes	Yes	
Power on Delay		Yes	Yes	Yes	
Daylight Saving Time		Yes	Yes	Yes	
Beacon	Yes	Yes	Yes		
HDMI-CEC	Yes	Yes	Yes		
SI Server Setting	Yes	Yes	Yes		
webRTC	Yes	Yes	Yes		
ENVIRONMENT CONDITIONS	Operation Temperature	32°F to 104°F / 0 °C to 40 °C	32°F to 104°F / 0 °C to 40 °C	32°F to 104°F / 0 °C to 40 °C	
	Operation Humidity	10 % to 80 %	10 % to 80 %	10 % to 80 %	
POWER	Power Supply	100-240V-, 50/60Hz	100-240V-, 50/60Hz	100-240V-, 50/60Hz	
	Power Type	Built-In Power	Built-In Power	Built-In Power	
	Power Switch	No	No	No	
SOUND	Speaker	No	No	No	
	Safety	IEC 60950-1 / EN 60950-1 / UL 60950-1			
CERTIFICATION	EMC	FCC Class "A" / CE / KC	FCC Class "A" / CE / KC	FCC Class "A" / CE / KC	
	OPS type compatible	Yes	Yes	Yes	
MEDIA PLAYER COMPATIBILITY	External Media player Attachable	Yes	Yes	Yes	
	SuperSign CMS	Yes	O(CMS)	O(CMS)	
SOFTWARE COMPATIBILITY	SuperSign Control / Control+	Yes	O(CMS)	O(CMS)	
	SuperSign White Balance	Yes (Sensor Only)	Yes (Sensor Only)	Yes (Sensor Only)	
	Signage 365 Care	Yes	Yes	Yes	
LANGUAGE	Languages	English, French, German, Spanish, Italian, Korean, Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portugues(Europe), Dutch, Czech, Greek			
	Accessories	Remote Controller(include battery 2ea), Power Cord, OS, HDMI Cable, Regulation Book, Phone to RS232C Gender			
ACCESSORIES & OTHER	Warranty	3 Year Limited	3 Year Limited	3 Year Limited	
	UPC	7 19192 63070 3	7 19192 63069 7	7 19192 63068 0	

<http://www.lg.com/us/business/commercial-display>
<http://www.twitter.com/LGCommDisplays>
<http://www.facebook.com/LGCommercialDisplays>
<http://www.linkedin.com/company/lg-commercial-displays-usa>
<http://www.youtube.com/lgcommercialdisplayusa>

LG may make changes to specifications and product descriptions without notice.
 For more detailed information on product specifications, please go to the appropriate product information page on <https://www.lg.com/us/business>. © Copyright 2019 LG Electronics USA, Inc. All rights reserved. LG and the LG logo are registered trademarks of LG Corp.
 SPEC_UH5E_051923_PR

