
Incredible Immersion with Ultra-Narrow Bezel

49VL5F

The 49VL5F provides all-encompassing screen immersion thanks to its narrow 3.5 mm bezel-to-bezel, while its outstanding IPS panel delivers a clear image from any angle. With its extremely attractive and highly functional design, it can be used to deliver advertising and information in a variety of business environments.



Incredible Immersion with Ultra-Narrow Bezel

49VL5F

Achieving Incredible Immersion

Seamless Large Screens with Ultra-Narrow Bezel

The narrow bezel creates a visually stunning digital wall to effectively deliver dynamic content and immerse the viewers. The large viewing area it generates is enough to captivate the attention of passersby.



Image Gap Reduction

The 49VL5F includes an image improvement algorithm that can reduce image gaps among tiled displays when playing back videos. Objects located on the bezel boundaries are adjusted for a seamless viewing experience.



Vivid and Dynamic Picture Quality

Higher Viewing Angle

Large screens are usually positioned higher than human-eye level, making uniform picture quality essential for video walls. The viewing angle of the 49VL5F is high enough to display vivid colors throughout the screen with no distortion.



45* High Viewing Angle

Wider Viewing Angle

It is well known that LG IPS panel technology enables better control of liquid crystals, which in turn allows the screen to be viewed from virtually any angle. Because of this, the 49VL5F captures the attention of and captivates more viewers with lifelike colors, regardless of their viewing position.



* The "Conventional" refers to displays which do not include an image improvement algorithm.


Incredible Immersion with Ultra-Narrow Bezel

49VL5F

User Convenience

Easy Color Adjustment

Depending on the content, the color temperature of the display can be easily adjusted in increments of 100K using a remote control.




Simple White Balance Adjustment

In conventional video walls, white balance was adjustable only in "full-white" mode, but the 49VL5F allows you to modify each value of gray scale to achieve more detailed and precise white balance adjustment.




User-Friendly Menu Structure

The menu structure has been optimized for commercial use. It simplifies approach flows and groups similar functions together, adopting a more intuitive user interface for ease of use. This way, users can avoid having to do trial-and-error when exploring desired functions and managing displays.



Intuitive GUI


The GUI(Graphic User Interface) is carefully designed with a four-way navigation remote control that lets users easily switch to other settings. Also, it adopts a larger font for better visibility, which is necessary when users want to control displays from relatively far distances.




* Results based on in-house testing. Actual test results may differ depending on environment and measuring equipment.

Dimensions

49"



Connectivity



- 1 HDMI IN 1
- 2 DVI-D IN
- 3 DP IN
- 4 DP OUT
- 5 USB 2.0 IN
- 6 RGB IN
- 7 AUDIO IN
- 8 AUDIO OUT
- 9 LAN IN
- 10 IR IN
- 11 RS232C IN
- 12 RS232C OUT



Specifications

49VL5F

	Screen Size	49"	
	Panel Technology	IPS	
	Aspect Ratio	16 : 9	
	Native Resolution	1,920 x 1,080 (FHD)	
	Brightness (Typ.)	450 nits	
	Contrast Ratio	1,300:1	
	Dynamic CR	500,000:1	
PANEL	Viewing Angle (H x V)	178° x 178°	
	Color Depth	1.07 Billion	
	Response Time	8 ms (G to G)	
	Surface Treatment	Haze 3%	
	Life Time (Typ.)	50,000 Hrs	
	Operation Hours	24 Hrs	
	Orientation	Landscape & Portrait	
	CONNECTIVITY	Input	HDMI, DP, DVI-D, RGB, Audio, USB 2.0
		Output	DP, Audio
		External Control	RS232C In/out, RJ45 (LAN) In, IR In
MECHANICAL SPECIFICATION	Bezel Color	Black	
	Bezel Width	2.3 mm (T/L), 1.2 mm (B/R)	
	Monitor Dimension (W x H x D)	42.43" x 23.9" x 3.5" / 1,077.6 x 607.8 x 89.7 mm	
	Weight (Head)	39.2 lbs / 17.8 kg	
	Carton Dimensions (W x H x D)	47.8 x 30.6" x 10.4" / 1,214 x 778 x 263 mm	
	Packed Weight	50.3 lbs / 22.8 kg	
	Handle	Yes	
	VESA™ Standard Mount Interface	600 x 400	
	KEY FEATURE		Temperature Sensor, Tile Mode (Up to 15x15), Natural Mode@Tile Mode, ISM Method, DPM Select, Smart Energy Saving, USB Cloning, Easy Brightness Control, Contents Scheduling (USB), Calibration Mode, Sync Mode, PM Mode, HDMI-CEC ¹⁾ , Wake on LAN, OSD Portrait Mode, Fail Over, No Signal Image, OPS Power Control, Scan Inversion (with Pivot Mode)
ENVIRONMENT CONDITIONS	Operation Temperature	32°F to 104°F / 0°C to 40°C	
	Operation Humidity	10% to 80%	
	Power Supply	100-240V~, 50/60Hz	
POWER	Power Type	Built-In Power	
	Power Consumption	Typ. 90 W Max. 110 W Smart Energy Saving 55 W	
	CERTIFICATION	Safety	IEC 60950-1 / EN 60950-1 / UL 60950-1
		EMC	UL / cUL / CB / TUV / KC
MEDIA PLAYER COMPATIBILITY	ErP / Energy Star	N/A / Yes (Energy Star 7.0)	
	OPS Type Compatible	No	
	External Media Player Attachable	Yes (MP500/MP700)	
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS	
	Control and Monitoring Software	SuperSign Control/Control+	
ACCESSORIES	Basic	Remote Controller, Power Cord, RS232C Cable, LAN Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual	
	Optional	Wall Mount (Landscape: WM-L640V, Portrait: WM-P640V)	
OTHER	Warranty	3 Year Limited	
	UPC	7 19192 63164 9	

1) Compatibility may differ by equipment.

- <http://www.lg.com/us/business/commercial-display>
- <http://www.twitter.com/LGCommDisplays>
- <http://www.facebook.com/LGcommercialdisplays>
- <http://www.linkedin.com/company/lg-commercial-displays-usa>
- <http://www.youtube.com/lgcommercialdisplayusa>

LG may make changes to specifications and product descriptions without notice. For more detailed information on product specifications, please go to the appropriate product information page on <https://www.lg.com/us/business>. © Copyright 2019 LG Electronics USA, Inc. All rights reserved. LG and the LG logo are registered trademarks of LG Corp. SPEC_49VL5F_051938_PR

