5.0 cu. ft. Front Load Washer

- 5.0 cu. ft. Mega Capacity
- 6Motion™ Technology
- 8 Cycles / 8 Options
- ColdWash[™] Option
- Direct Drive Motor (10-Year Limited Warranty)
- NeveRust™ Stainless Steel Tub
- SmartDiagnosis™







COLOR AVAILABILITY	
WM3470CM – Middle Black	
WM3470CW - White	
CAPACITY & MATCHING DRYERS	
Capacity (cu. ft.)	5.0
Matching Electric Dryer	DLE3470M, DLE3470W
Matching Gas Dryer	DLG3471M, DLG3471W
APPEARANCE	
Electronic Controls with LED Display	Yes
Hard Buttons	Yes
Touch Buttons	Yes
Dial-A-Cycle™	Yes
ENERGY & WATER	
ENERGY STAR® Certified	Yes
CEE Qualified	Tier 2
Integrated Modified Energy Factor (IMEF)	2.92
Integrated Water Factor (IWF)	2.9
WASH CYCLES	
Number of Cycles	8
Wash Cycles	Normal, Perm. Press, Heavy Duty, Delicates, Towels, Speed Wash, Bedding, Tub Clean
WASH OPTIONS	
Number of Options	8
Options	Pre-wash, Delay Wash, Cold Wash, Extra Rinse, Rinse+Spin, Control Lock, Spin Only, Signal

WASH DETAILS		
Internal Heater	No	
Number of Wash / Rinse Temps	5	
Wash / Rinse Temps	Tap Cold, Cold, Semi Warm, Warm, Hot	
Number of Spin Speeds	5	
Spin Speeds	Extra High, High, Medium, Low, No Spin	
Max RPM	1,300	
Water Levels	Load Sensing	
Number of Soil Levels	3	
AAFA Certified	No	
FABRIC CARE		
AI DD™	No	
Wash Technology	Standard	
Steam Technology	No	
Allergiene® Cycle	No	
Sanitary Cycle	No	
ColdWash™ Option	Yes	
Al Fabric Sensor	No	
Soil Level Sensor	No	
CONVENIENCE		
Vibration Sensing (Cabinet Vibration Sensor)	No	
TrueBalance™ Anti-Vibration System	Yes	
Dispenser Type	4-Tray (Prewash, Main Wash with Liquid Detergent Cup, Bleach, Fabric Softener)	
Drum Light	No	
End of Cycle Signal	Yes	
LoadSense	Yes	
Control Lock	Yes	
Auto Suds Removal	Yes	
4 Adjustable Leveling Legs	Yes	
ADA Compliant	No	

SMART FEATURES	
Wi-Fi Enabled	No
ThinQ® Technology	No
ThinQ Care	No
Voice Control	No
SmartDiagnosis™	Yes
Remote Start (On / Off)	No
Remote Monitoring & Notifications	No
Energy Monitoring	No
Tub Clean Coach	No
MOTOR AND AGITATOR	·

Axis	Horizontal
MATERIALS AND FINISHES	
NeveRust™ Stainless Steel Drum	Yes
Cabinet	Painted Steel
Control Panel	Plastic
Top Plate	Painted Steel
Door / Rim	Glass/White Rim (White)

Inverter Direct Drive Motor

Glass/Silver Rim (Middle Black)

3-Prong (Cord Attached to Unit)

Door Cover	Clear Round Cover	
TECHNICAL SPECS		
Electrical Requirements	120V, 60 Hz, 10 Amps	
Type Electric		
Power Outlet Location	Within 60" of Either Side	

20 - 120 psi

Min. / Max. Water Pressure INCLUDED ACCESSORIES

Motor Type

Plug Type

Drain Hose, Non-Skid Pads, Hole Caps, Wrench, Tie Strap, Elbow Bracket (for Securing Drain Hose)


bracket (for Securing brain riose)		
OPTIONAL ACCESSORIES		
Pedestal	WDP6M, WDP6W	
Pedestal (W x H x D)	27" x 13 5/₈ " x 28"	
ADA-Compliant Pedestal Riser	WDPS2W (White only)	
ADA-Compliant Pedestal Riser (W x H x D)	27" x 5 1/₈ " x 27 1/₂ "	
LG Sidekick™ Pedestal Washer	WD300CW (White only)	
LG Sidekick™ Pedestal Washer (W x H x D)	27" x 14 1/ ₈ " x 30 3/ ₄ "	
Stacking Kit	KSTK4	
DIMENSIONS		
Product (W x H x D)	27" x 39" x 33 1/8 "	
Depth with Door Open	57 3 / 4 "	
Cutout Dimensions (W x H x D)	29" x 39 1/₄ " x 37 1/₄ "	
Carton Dimensions (W x H x D)	29 1/2" x 42 1/8" x 34 1/4"	
Approx. Weight (Product / Carton)	191.8 lbs. / 207.5 lbs.	


LIMITED WARRANTY	
Parts and Labor	1 Year
Direct Drive Motor	10 Years (Parts Only)
Drum	3 Years (Parts Only)

DIMENSIONS / CLEARANCES

FLOOR INSTALLATION

To ensure sufficient clearance for water inlet hoses, drain hose and airflow, allow minimum clearances of at least 1 inch (2.5 cm) at the sides and 4 inches (10 cm) behind the washer. Be sure to allow for wall, door, or floor moldings that may increase the required clearances.







DIM	DIMENSIONS / CLEARANCES	
Α	57 3/₄ '' (146.6 cm)	
В	33 1/8 " (84 cm)	
С	4'' (10 cm)	
D	1" (2.5 cm)	
Е	27" (70 cm)	
F	1/ ₄ " (0.5 cm)	

STACKING OR PEDESTAL INSTALLATION

The washer can be stacked under a dryer or on top of a pedestal or pedestal washer.





DIM	DIMENSIONS / CLEARANCES	
Α	33 1/8 " (84 cm)	
В	4'' (10 cm)	
С	1" (2.5 cm)	
D	27'' (70 cm)	
Е	77 1 / 2 " (196.8 cm)	
F	1/ ₄ " (0.5 cm)	

