







DLE2101 DLG2102

Electric/Gas Dryers



LG offers highly stylized designs in the front load industry. With laundry moving out of the basement and closer to the living areas, style has become an important element in the purchase process.

Available colors:

() White

PERFORMANCE

- XL Capacity (7.3 cu.ft.)
- Sensor Dry System for Intelligent Fabric Care and Energy Efficiency
- 7 Drying Programs
- 5 Temperature Levels
- Wrinkle Care Option
- Delicates Cycle

STYLE AND DESIGN

- Upfront Electronic Control Panel with Dial-A-Cycle™
- Chrome Door with Glass
- Stackable with Matching Washer
- Optional Matching Drawer Pedestal

TECHNOLOGY BENEFITS

LoDecibel[™] Quiet Operation

DLE2101 DLG2102

Electric/Gas Dryers



Electronic Control Panel with Dial-A-Cycle™

Intuitive controls allow you to 'set it and go'. You can also save your favorite dry cycle by pressing Custom Program. You'll have optimized drying performance with the push of a button.

LoDecibel™ Quiet Operation

Anti-Vibration motor and one piece cabinet structure reduce unnecessary noises.

Wrinkle Care Cycle

Dry clothes are periodically tumbled without heat to reduce wrinkles.

Sensor Dry System

Measures moisture in the drum during the cycle, then automatically adjusts the drying time and temperature for enhanced fabric care.



Design and specifications are subject to change without notice.
© 2009 LG Electronics U.S.A., Inc., Englewood Cliffs, N.J.
All Rights Reserved. LG Design and Life's Good are trademarks of LG Electronics Inc.
All other trademarks are the property of their respective owners.

LG Electronics U.S.A., Inc.

1000 Sylvan Avenue, Englewood Cliffs, NJ 07632 Customer Service and Technical Support: (800) 243-0000

ont Loader
sign Look Front Cont
elligent Electronic Controls
al-A-Cycle™
pacity 7.3 cu
y Linen Capacity >10.1
RYING PROGRAMS
Programs Sensor Dry: Cotton/Towels, Norm
Perm Press, Delicate
Manual Dry: Speed Dry, Air Dry, Freshen U
Wrinkle Care, More Time, Less Tin
Temperature Levels High, Medium Hig
Medium, Low, Ultra Lo
Orying Levels Very Dry, More Dry, Normal D
Less Dry, Damp D
y Times 60 min., 50 min., 40 min., 30 mi
20 min., More Time/Less Tin
BRIC CARE FEATURES
nsor Dry
ecise Temperature Control with Variable Heater
DNVENIENCE FEATURES
d of Cycle Beeper Variab
ild Lock
nting Option Electric: 4 Way Venti
Gas: 3 Way Ventii
um Light
versible Door
maining Time Display/Status Indicator(s)
veling Legs 4 Adjustable Le
Decibel™ Quiet Operation
ATERIALS AND FINISHES
um Aluminized Alloy Ste
p Plate Paint
binet Painted Ste
introl Panel Plas
insparent Door Glass
or Rim Chron
11.11.01
ailable Colors White (
allable Colors White (\ DWER SOURCE
OWER SOURCE
WER SOURCE tings UL List
DWER SOURCE tings UL List quirements 120V, 15 Amps/240V, 30 Am
DWER SOURCE UL List fings UL List quirements 120V, 15 Amps/240V, 30 Am pe Gas / Elect
DWER SOURCE UL List tings 120V, 15 Amps/240V, 30 Am oe Gas / Elect
WER SOURCE tings UL List quirements 120V, 15 Amps/240V, 30 Am to Gas / Elect PTIONS destal WDP3
DWER SOURCE fings UL List quirements 120V, 15 Amps/240V, 30 Amps pe Gas / Elect PTIONS WDP3 destal WDP3 destal (WxHxD) 27" x 13 3/5" x 28 2/
DWER SOURCE fings UL List quirements 120V, 15 Amps/240V, 30 Am De Gas / Elect PTIONS WDP3 destal WDP3 destal (WXHxD) 27" x 13 3/5" x 28 2/ scking Kit WST
DWER SOURCE tings UL List quirements 120V, 15 Amps/240V, 30 Am Die Gas / Elect PTIONS WDP3 destal WDP3 destal (WXHXD) 27" x 13 3/5" x 28 2/3 acking Kit WST MENSIONS WST
SOURCE UL List
SOURCE UL List
SOURCE
SOURCE UL List
SOURCE ### SOURCE ### UL List ### 120V, 15 Amps/240V, 30 Am ### pe
SOURCE UL List
SOURCE ### SOURCE ### UL List ### 120V, 15 Amps/240V, 30 Am ### pe
SOURCE
SOURCE ### SO
SOURCE tings